

102244

County Swift
Quad Big Bend
Quad ID 130A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/17/1988
Update Date 08/19/2021
Received Date

Well Name WEISS,					Township 120	Range 41	Dir W	Section 8	Subsection ABBCCA	Well Depth 98 ft.				Depth Completed 98 ft.				Date Well Completed 10/25/1979							
Elevation 1032					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Cable Tool				Drill Fluid											
Address C/W APPLETON MN 56208										Use domestic				Status Active											
Stratigraphy Information Geological Material From To (ft.) Color Hardness SOIL 0 1 BLACK CLAY 1 19 YELLOW SOFT CLAY 19 51 BLUE SOFT CLAY 51 72 BLUE HARD SANDY CLAY 72 85 BLUE SOFT CLAY 85 90 BLUE HARD SAND 90 98 GRAY										Well Hydrofractured? Yes ☐ No ☐				From To											
										Casing Type Single casing				Joint Threaded											
										Drive Shoe? Yes ☒ No ☐				Above/Below 1 ft.											
										Casing Diameter 5 in.				Weight 94 ft. 15 lbs./ft.											
										Open Hole From ft. To ft.															
										Screen? ☒				Type stainless				Make JOHNSON							
										Diameter 4 in.				Slot/Gauze 12				Length 4 ft.				Set 94 ft. 98 ft.			
										Static Water Level 20 ft.				land surface				Measure 10/25/1979							
										Pumping Level (below land surface) 21 ft.				4 hrs. Pumping at				12 g.p.m.							
										Wellhead Completion Pitless adapter manufacturer				Model											
☐ Casing Protection				☐ 12 in. above grade																					
☐ At-grade (Environmental Wells and Borings ONLY)																									
Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified																									
Nearest Known Source of Contamination 150 feet West Direction				Septic tank/drain field Type																					
Well disinfected upon completion? ☒ Yes ☐ No																									
Pump ☐ Not Installed Date Installed 10/25/1979																									
Manufacturer's name GOULDS																									
Model Number 10EJ103412 HP 0.5 Volt 220																									
Length of drop pipe 49 ft Capacity 12 g.p. Typ Submersible																									
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																									
Miscellaneous First Bedrock Aquifer Quat. buried																									
Last Strat sand-gray Depth to Bedrock ft																									
Located by Minnesota Geological Survey																									
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)																									
System UTM - NAD83, Zone 15, Meters X 278027 Y 5011604																									
Unique Number Verification Plat Book Input Date 06/12/1996																									
Angled Drill Hole																									
Well Contractor Jacobs & Grant Well 12073 PAYNE, C.																									
Licensee Business Lic. or Reg. No. Name of Driller																									
Remarks																									
Minnesota Well Index Report					102244					Printed on 08/13/2026 HE-01205-15															