

113870

County Morrison
Quad Upsala
Quad ID 177D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/13/1988
Update Date 02/14/2014
Received Date

Well Name WALCH, JANET					Township 128	Range 31	Dir W	Section 32	Subsection ADDDCD	Well Depth 63 ft.		Depth Completed 63 ft.		Date Well Completed 10/17/1977							
Elevation 1255		Elev. Method 7.5 minute topographic map (+/- 5 feet)		Drill Method Cable Tool										Drill Fluid							
Address Well SWANVILLE MN 56382										Use domestic		Status Active									
Stratigraphy Information Geological Material From To (ft.) Color Hardness COARSE GRAVEL & 0 35 BROWN CLAY 35 55 BLUE SAND 55 63 GRAY										Well Hydrofractured?		Yes ☐		No ☐		From		To			
										Casing Type		Single casing		Joint		Threaded					
										Drive Shoe?		Yes ☐		No ☐		Above/Below		1 ft.			
										Casing Diameter		Weight									
										4 in.		To 59 ft.		lbs./ft.							
										Open Hole		From		ft.		To		ft.			
										Screen?		☒		Type		stainless		Make		JOHNSON	
										Diameter		Slot/Gauze		Length		Set					
										4 in.		18		4 ft.		59 ft.		63 ft.			
										Static Water Level		42 ft.		land surface		Measure		10/17/1977			
Pumping Level (below land surface)										42 ft.		1 hrs.		Pumping at 15 g.p.m.							
Wellhead Completion										Pitless adapter manufacturer		Model									
☐ Casing Protection										☒ 12 in. above grade											
☐ At-grade (Environmental Wells and Borings ONLY)																					
Grouting Information										Well Grouted?		☐ Yes		☒ No		☐ Not Specified					
Nearest Known Source of Contamination										feet		Direction		Type							
Well disinfected upon completion?										☒ Yes		☐ No									
Pump										☐ Not Installed		Date Installed		06/04/1978							
Manufacturer's name										RED JACKET											
Model Number										501		HP		0.5		Volt 230					
Length of drop pipe										41 ft		Capacity		15 g.p.		Typ Submersible					
Abandoned										Does property have any not in use and not sealed well(s)?		☐ Yes		☐ No							
Variance										Was a variance granted from the MDH for this well?		☐ Yes		☐ No							
Miscellaneous										First Bedrock		Aquifer		Quat. buried							
Last Strat										sand-gray		Depth to Bedrock		ft							
Located by										Minnesota Geological Survey											
Locate Method										Digitized - scale 1:24,000 or larger (Digitizing Table)											
System										UTM - NAD83, Zone 15, Meters		X 375990		Y 5079053							
Unique Number Verification										Other, note in		Input Date		04/12/1995							
Angled Drill Hole																					
Well Contractor										Eckstrom Well		49101		ECKSTROM, D.							
Licensee Business										Lic. or Reg. No.		Name of Driller									