

118870

County Hennepin
Quad Hamel
Quad ID 121D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 08/24/1991
Update Date 02/14/2014
Received Date

Well Name CARRINGER,	Township 119	Range 22	Dir W	Section 32	Subsection BCCB	Well Depth 209 ft.	Depth Completed 209 ft.	Date Well Completed 05/24/1978
Elevation 952 ft.	Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Cable Tool	Drill Fluid	
Address Well 6590 LAWNDALE LA MAPLE GROVE MN 55369						Use domestic	Status Active	
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☐	From	To
						Casing Type Single casing	Joint Threaded	
						Drive Shoe? Yes ☒ No ☐	Above/Below 1 ft.	
Geological Material						Casing Diameter	Weight	
TOP SOIL						4 in.	To	203 ft. 11 lbs./ft.
CLAY								
CLAY SANDY								
CLAY								
CLAY								
CLAY SANDY								
SANDROCK								
						Open Hole	From	ft. To
						Screen? ☒	Type stainless	Make JOHNSON
						Diameter	Slot/Gauze	Length
						4 in.	10	8.5 ft. 201 ft. 209 ft.
						Static Water Level		
						65 ft.	land surface	Measure 05/24/1978
						Pumping Level (below land surface)		
						Wellhead Completion		
						Pitless adapter manufacturer Model		
						☐ Casing Protection ☒ 12 in. above grade		
						☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information	Well Grouted?	☐ Yes ☒ No ☐ Not Specified
						Nearest Known Source of Contamination		
						50 feet	<u>Southeas</u> Direction	<u>Septic tank/drain field</u> Type
						Well disinfected upon completion? ☒ Yes ☐ No		
						Pump ☐ Not Installed	Date Installed	05/30/1978
						Manufacturer's name RED JACKET		
						Model Number	HP 0.75	Volt 230
						Length of drop pipe	105 ft	Capacity 11 g.p. Typ Submersible
						Abandoned		
						Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No		
						Variance		
						Was a variance granted from the MDH for this well? ☐ Yes ☐ No		
						Miscellaneous		
						First Bedrock	Jordan Sandstone	Aquifer multiple
						Last Strat	Jordan Sandstone	Depth to Bedrock 209 ft
						Located by Minnesota Geological Survey		
						Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)		
						System	UTM - NAD83, Zone 15, Meters	X 460541 Y 4991337
						Unique Number Verification	Address verification	Input Date 01/01/1990
						Angled Drill Hole		
						Well Contractor		
						Pumarlo Well Co.	27023	PUMARLO, F.
						Licensee Business	Lic. or Reg. No.	Name of Driller