

124970

County Hennepin
Quad Osseo
Quad ID 120C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 08/24/1991
Update Date 02/14/2014
Received Date

Well Name Township Range Dir Section Subsection 119 22 W 34 CABADD					Well Depth 97 ft.		Depth Completed 97 ft.		Date Well Completed 03/07/1977	
Elevation 955 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary		Drill Fluid			
Address Well 6449 ZINNIA LA N MAPLE GROVE MN 55369					Use domestic		Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 21 YELLOW MEDIUM CLAY 21 45 GRAY MEDIUM GRAVEL 45 48 BROWN M.SOFT CLAY GRAVELLY 48 88 RED M.HARD SAND 88 97 BROWN SOFT					Well Hydrofractured? Yes ☐ No ☐ From To					
					Casing Type Single casing Joint Threaded					
					Drive Shoe? Yes ☒ No ☐ Above/Below 1 ft.					
					Casing Diameter Weight 4 in. To 93 ft. 11 lbs./ft.					
					Open Hole From ft. To ft.					
					Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 4 in. 12 4 ft. 93 ft. 97 ft.					
					Static Water Level 65 ft. land surface Measure 03/07/1977					
					Pumping Level (below land surface) 80 ft. 2 hrs. Pumping at 30 g.p.m.					
					Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)					
					Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 0 ft. 93 ft. cuttings ft. ft.					
Nearest Known Source of Contamination 20 feet South Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No										
Pump ☐ Not Installed Date Installed 03/08/1977 Manufacturer's name FLINT & WALLING Model Number 5BA8 HP 0.5 Volt 230 Length of drop pipe 84 ft Capacity 12 g.p. Typ Submersible										
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No										
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No										
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table) System UTM - NAD83, Zone 15, Meters X 464244 Y 4991062 Unique Number Verification Address verification Input Date 01/01/1990										
Angled Drill Hole										
Well Contractor Ruppert & Son 27086 CLARK, F. Licensee Business Lic. or Reg. No. Name of Driller										
Remarks										

Minnesota Well Index Report

124970

Printed on 08/13/2026
HE-01205-15