

126066

County Isanti
Quad Isanti
Quad ID 135B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/09/1990
Update Date 02/14/2014
Received Date 06/01/1976

Well Name DAVIS, ROY					Township 34		Range 23		Dir Section W 4		Subsection CDBABD		Well Depth 59 ft.		Depth Completed 59 ft.		Date Well Completed 05/03/1976																																			
Elevation 931 ft.					Elev. Method		7.5 minute topographic map (+/- 5 feet)										Drill Method Jetted		Drill Fluid																																	
Address														Use domestic		Status Active																																				
C/W RR 2 ISANTI MN 55040														Well Hydrofractured? Yes ☐ No ☐ From To																																						
Stratigraphy Information														Casing Type Single casing		Joint Threaded																																				
<table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SUGAR SAND</td><td>0</td><td>15</td><td>TAN</td><td>SOFT</td></tr><tr><td>COARSE SAND</td><td>15</td><td>20</td><td>TAN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>20</td><td>32</td><td>YELLOW</td><td>SFT-HRD</td></tr><tr><td>COARSE SAND</td><td>32</td><td>41</td><td>BLK/BRN</td><td>SOFT</td></tr><tr><td>CLAY & SAND</td><td>41</td><td>52</td><td>BROWN</td><td>SFT-HRD</td></tr><tr><td>WATER GRAVEL</td><td>52</td><td>59</td><td>VARIED</td><td>SOFT</td></tr></table>														Geological Material	From	To (ft.)	Color	Hardness	SUGAR SAND	0	15	TAN	SOFT	COARSE SAND	15	20	TAN	SOFT	CLAY	20	32	YELLOW	SFT-HRD	COARSE SAND	32	41	BLK/BRN	SOFT	CLAY & SAND	41	52	BROWN	SFT-HRD	WATER GRAVEL	52	59	VARIED	SOFT	Drive Shoe? Yes ☒ No ☐		Above/Below 1 ft.	
Geological Material	From	To (ft.)	Color	Hardness																																																
SUGAR SAND	0	15	TAN	SOFT																																																
COARSE SAND	15	20	TAN	SOFT																																																
CLAY	20	32	YELLOW	SFT-HRD																																																
COARSE SAND	32	41	BLK/BRN	SOFT																																																
CLAY & SAND	41	52	BROWN	SFT-HRD																																																
WATER GRAVEL	52	59	VARIED	SOFT																																																
Casing Diameter Weight																																																				
2 in. To 54 ft. 3.75 lbs./ft.																																																				
Open Hole From ft. To ft.																																																				
Screen? ☒ Type stainless Make JOHNSON																																																				
Diameter Slot/Gauze Length Set																																																				
1.3 in. 10 5 ft. 54 ft. 59 ft.																																																				
Static Water Level																																																				
25 ft. land surface Measure 05/03/1976																																																				
Pumping Level (below land surface)																																																				
28 ft. 2 hrs. Pumping at 15 g.p.m.																																																				
Wellhead Completion																																																				
Pitless adapter manufacturer Model																																																				
☐ Casing Protection ☐ 12 in. above grade																																																				
☐ At-grade (Environmental Wells and Borings ONLY)																																																				
Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified																																																				
Nearest Known Source of Contamination																																																				
100 feet West Direction Body of water Type																																																				
Well disinfected upon completion? ☒ Yes ☐ No																																																				
Pump ☐ Not Installed Date Installed 05/25/1976																																																				
Manufacturer's name JACUZZI																																																				
Model Number SRP2 HP 0.5 Volt 115																																																				
Length of drop pipe 21 ft Capacity 8 g.p. Typ Jet																																																				
Abandoned																																																				
Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																																				
Variance																																																				
Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																																				
Miscellaneous																																																				
First Bedrock Aquifer Quat. buried																																																				
Last Strat gravel (+larger) Depth to Bedrock ft																																																				
Located by Minnesota Geological Survey																																																				
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)																																																				
System UTM - NAD83, Zone 15, Meters X 482983 Y 5034161																																																				
Unique Number Verification Name on mailbox Input Date 04/17/1995																																																				
Angled Drill Hole																																																				
Well Contractor																																																				
Labore Well Co 62040 LABORE, L.																																																				
Licensee Business Lic. or Reg. No. Name of Driller																																																				
Remarks																																																				