

156116

County Anoka
Quad Coon Lake
Quad ID 135C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/15/1991
Update Date 02/14/2014
Received Date

Well Name NUE, PATRICK					Township 33	Range 23	Dir W	Section 34	Subsection CCCAAB	Well Depth 112 ft.				Depth Completed 112 ft.				Date Well Completed 06/02/1980							
Elevation 914 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Cable Tool				Drill Fluid											
Address C/W 2647 181ST LA NE MN										Use domestic				Status Active											
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 27 BROWN SOFT SAND 27 43 GRAY SOFT SAND & CLAY 43 76 GRAY SOFT GRAVEL & CLAY 76 90 RED SOFT HARDPAN 90 96 BLACK HARD SAND 96 112 BROWN SOFT										Well Hydrofractured? Yes ☐ No ☐				From To											
										Casing Type Single casing				Joint Threaded											
										Drive Shoe? Yes ☒ No ☐				Above/Below 1 ft.											
										Casing Diameter 4 in.				Weight 108 ft. 11 lbs./ft.											
										Open Hole From ft. To ft.															
										Screen? ☒				Type stainless				Make SMITH							
										Diameter 2 in.				Slot/Gauze 8				Length 6 ft.				Set 108 ft. 112 ft.			
										Static Water Level 15 ft.				land surface				Measure 06/02/1980							
										Pumping Level (below land surface) 25 ft.				3 hrs. Pumping at				20 g.p.m.							
										Wellhead Completion Pitless adapter manufacturer								Model							
☐ Casing Protection				☒ 12 in. above grade																					
☐ At-grade (Environmental Wells and Borings ONLY)																									
Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified																									
Nearest Known Source of Contamination 100 feet Southwes Direction								Septic tank/drain field Type																	
Well disinfected upon completion? ☒ Yes ☐ No																									
Pump ☐ Not Installed				Date Installed 06/02/1980																					
Manufacturer's name PIONEER																									
Model Number HP 0.5				Volt 230																					
Length of drop pipe 42 ft				Capacity 20 g.p.				Typ Submersible																	
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																									
Miscellaneous First Bedrock Aquifer Quat. buried																									
Last Strat sand-brown				Depth to Bedrock ft																					
Located by Minnesota Geological Survey																									
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)																									
System UTM - NAD83, Zone 15, Meters				X 484182 Y 5016214																					
Unique Number Verification				Address verification				Input Date 01/01/1990																	
Angled Drill Hole																									
Well Contractor Perron Well Co. 62414 NIEKEN, L.																									
Licensee Business				Lic. or Reg. No.				Name of Driller																	
Remarks SOUTH 0.5 SECTION																									
Minnesota Well Index Report					156116					Printed on 08/13/2026 HE-01205-15															