

163746

County Anoka
Quad Centerville
Quad ID 119A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/15/1991
Update Date 04/20/2026
Received Date

Well Name REINKE, SCOTT					Township 31		Range 22		Dir Section W 8		Subsection DAADBB		Well Depth 262 ft.		Depth Completed 262 ft.		Date Well Completed 07/17/1979																								
Elevation 902.2					Elev. Method		LiDAR 1m DEM (MNDNR)										Drill Method Non-specified Rotary		Drill Fluid																						
Address													Use domestic		Status Active																										
C/W 7768 CAROLE DR LINO LAKES MN													Well Hydrofractured? Yes ☐ No ☐					From		To																					
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY & SAND</td><td>0</td><td>75</td><td></td><td></td></tr><tr><td>CLAY</td><td>75</td><td>201</td><td></td><td></td></tr><tr><td>GRAVEL</td><td>201</td><td>245</td><td></td><td></td></tr><tr><td>SANDROCK</td><td>245</td><td>262</td><td></td><td></td></tr></table>													Geological Material	From	To (ft.)	Color	Hardness	CLAY & SAND	0	75			CLAY	75	201			GRAVEL	201	245			SANDROCK	245	262			Casing Type Single casing		Joint Threaded	
													Geological Material	From	To (ft.)	Color	Hardness																								
													CLAY & SAND	0	75																										
													CLAY	75	201																										
													GRAVEL	201	245																										
													SANDROCK	245	262																										
													Drive Shoe? Yes ☒ No ☐		Above/Below 1 ft.																										
													Casing Diameter 4 in. To 252 ft. 11 lbs./ft.																												
													Open Hole From 252 ft. To 262 ft.																												
													Screen? ☐		Type		Make																								
Static Water Level 15 ft. land surface Measure 07/17/1979																																									
Pumping Level (below land surface) 50 ft. 2 hrs. Pumping at 60 g.p.m.																																									
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)													Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified																												
Nearest Known Source of Contamination 55 feet <u>Northeas</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No													Pump ☐ Not Installed Date Installed <u>07/31/1979</u> Manufacturer's name GOULD Model Number <u>10EX07412</u> HP <u>0.75</u> Volt <u>250</u> Length of drop pipe <u>80</u> ft Capacity g.p. Typ <u>Submersible</u>																												
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No													Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																												
Miscellaneous First Bedrock Tunnel City Group Aquifer Tunnel City Last Strat Tunnel City Group Depth to Bedrock 245 ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 491914 Y 5003882 Unique Number Verification Info/GPS from data Input Date 01/01/1990													Angled Drill Hole																												
Well Contractor Lauren McCullough Well 82443 ENGLER, K. Licensee Business Lic. or Reg. No. Name of Driller																																									

Remarks
SOUTH 0.5 SECTION CAROLE 1ST ADD. BLK 2 LOT 2