

168003

County Stearns
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/09/1989
Update Date 02/14/2014
Received Date

Well Name ROLLINS, TOM	Township 123	Range 30	Dir Section W 26	Subsection null	Well Depth 60 ft.	Depth Completed 52 ft.	Date Well Completed 06/19/1979
Elevation	Elev. Method				Drill Method Non-specified Rotary	Drill Fluid	
Address C/W RR 1 COLD SPRING MN					Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 45 BROWN MEDIUM SAND 45 60 GRAY SOFT					Well Hydrofractured? Yes ☐ No ☐ From To		
					Casing Type Single casing Joint Welded		
					Drive Shoe? Yes ☐ No ☐ Above/Below		
					Casing Diameter Weight 4 in. To 48 ft. lbs./ft.		
					Open Hole From ft. To ft.		
					Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 4 in. 15 4 ft. 48 ft. 52 ft.		
					Static Water Level 30 ft. land surface Measure 06/19/1979		
					Pumping Level (below land surface) 35 ft. 1 hrs. Pumping at 20 g.p.m.		
					Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
					Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified		
					Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No		
					Pump ☐ Not Installed Date Installed 09/26/1979 Manufacturer's name DEMPSTER Model Number 15-50 HP 0.5 Volt 230 Length of drop pipe 1 ft Capacity 31 g.p. Typ Submersible		
					Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No		
					Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No		
					Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date		
					Angled Drill Hole		
					Well Contractor Traut Well 73157 SYL & MIKE Licensee Business Lic. or Reg. No. Name of Driller		