

176905

County St. Louis
Quad Saginaw
Quad ID 245C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/22/1988
Update Date 02/14/2018
Received Date

Well Name COPISEY,					Township 50	Range 16	Dir Section W 6	Subsection DDBBDB	Well Depth 60 ft.				Depth Completed 60 ft.				Date Well Completed 06/09/1980			
Elevation 1373					Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary				Drill Fluid						
Address Well 6930 2 HY SAGINAW MN 55779 Contact 4350 LAVAQUE RD DULUTH MN									Use domestic								Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 50 RED SOFT GRAVEL 50 60 RED SOFT									Well Hydrofractured? Yes ☐ No ☐ From To											
									Casing Type Single casing Joint Threaded Drive Shoe? Yes ☒ No ☐ Above/Below 1 ft.											
									Casing Diameter Weight Hole Diameter 6 in. To 60 ft. 19 lbs./ft. 8.7 in. To 60 ft.											
									Open Hole From 60 ft. To 60 ft.											
									Screen? ☐ Type Make											
									Static Water Level 20 ft. land surface Measure 06/09/1980											
									Pumping Level (below land surface) 35 ft. 2 hrs. Pumping at 10 g.p.m.											
									Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)											
									Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 0 ft. 50 ft.											
									Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No											
									Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ											
									Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No											
									Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No											
									Miscellaneous First Bedrock Aquifer Quat. buried Last Strat gravel (+larger)-red Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 544885 Y 5187535 Unique Number Verification Address verification Input Date 08/27/2014											
									Angled Drill Hole											
									Well Contractor Lind Well Co. 93493 HOLLY, K Licensee Business Lic. or Reg. No. Name of Driller											
Remarks																				

Minnesota Well Index Report

176905

Printed on 08/13/2026
HE-01205-15