

178242

County Washington
Quad Scandia
Quad ID 134D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date06/12/1989

Update Date02/14/2014

Received Date

Well Name JENSEN,				Township 32	Range 20	Dir Section W 5	Subsection DBCBBB	Well Depth 57 ft.		Depth Completed 57 ft.		Date Well Completed 06/18/1981																								
Elevation 922 ft.		Elev. Method 7.5 minute topographic map (+/- 5 feet)		Drill Method Cable Tool								Drill Fluid																								
Address C/W23375 LOFTON AV N SCANDIA MN								Use domestic				Status Active																								
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>14</td><td></td><td></td></tr><tr><td>SAND</td><td>14</td><td>35</td><td></td><td></td></tr><tr><td>CLAY</td><td>35</td><td>42</td><td></td><td></td></tr><tr><td>WATERSAND</td><td>42</td><td>57</td><td></td><td></td></tr></table>								Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	14			SAND	14	35			CLAY	35	42			WATERSAND	42	57			Well Hydrofractured? Yes ☐ No ☐ From To			
								Geological Material	From	To (ft.)	Color	Hardness																								
								CLAY	0	14																										
								SAND	14	35																										
								CLAY	35	42																										
								WATERSAND	42	57																										
								Casing Type Single casing				Joint Threaded																								
								Drive Shoe? Yes ☒ No ☐				Above/Below 1 ft.																								
								Casing Diameter 4 in.				Weight 55 ft. 11 lbs./ft.																								
								Open Hole Fromft.Toft.																												
Screen? ☒				Type DiameterSlot/GauzeLengthSet				Make JOHNSON 236																												
2.5 in.				186 ft.				51 ft. 57 ft.																												
Static Water Level 13 ft. land surfaceMeasure06/18/1981																																				
Pumping Level (below land surface) 30 ft. 3 hrs. Pumping at20 g.p.m.																																				
Wellhead Completion Pitless adapter manufacturerModel ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																				
Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified																																				
Nearest Known Source of Contamination 60 feetSouth DirectionSeptic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																																				
Pump ☐ Not InstalledDate Installed06/25/1981 Manufacturer's nameRED JACKET Model NumberBVC 751HP0.75Volt220 Length of drop pipe30 ftCapacity15 g.p.TypSubmersible																																				
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																				
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																				
Miscellaneous First BedrockAquiferQuat. buried Last Strat sandDepth to Bedrockft Located byMinnesota Geological Survey Locate MethodDigitized - scale 1:24,000 or larger (Digitizing Table) SystemUTM - NAD83, Zone 15, MetersX 510561Y 5014855 Unique Number VerificationName on mailboxInput Date01/01/1990																																				
Angled Drill Hole																																				
Well Contractor McCullough & Sons82054MURRAY, R. Licensee BusinessLic. or Reg. No.Name of Driller																																				