

191051

County Hubbard
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/25/1990
Update Date 11/03/2014
Received Date

Well Name PARSON, Elevation	Township 140 Elev. Method	Range 33	Dir W	Section 11	Subsection BBC	Well Depth 40 ft.	Depth Completed 40 ft.	Date Well Completed 08/06/1982																								
Address Contact NEVIS MN 56467						Drill Method Jetted	Drill Fluid																									
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND</td><td>0</td><td>26</td><td>BROWN</td><td></td></tr><tr><td>HARDPAN</td><td>26</td><td>30</td><td></td><td>HARD</td></tr><tr><td>FINE SAND</td><td>30</td><td>35</td><td></td><td></td></tr><tr><td>COARSE SAND</td><td>35</td><td>40</td><td>BLUE</td><td></td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SAND	0	26	BROWN		HARDPAN	26	30		HARD	FINE SAND	30	35			COARSE SAND	35	40	BLUE		Use domestic	Status Active
						Geological Material	From	To (ft.)	Color	Hardness																						
						SAND	0	26	BROWN																							
						HARDPAN	26	30		HARD																						
						FINE SAND	30	35																								
						COARSE SAND	35	40	BLUE																							
						Well Hydrofractured? Yes ☐ No ☐			From To																							
						Casing Type Single casing			Joint																							
						Drive Shoe? Yes ☒ No ☐			Above/Below 8 ft.																							
						Casing Diameter 2 in. To 36 ft.			Weight lbs./ft.																							
Open Hole Screen? ☒			From ft. To ft.																													
Type galvanized			Make JOHNSON																													
Diameter 1.2 in.			Length 5 ft.																													
Set 36 ft.			40 ft.																													
Static Water Level 28 ft. land surface Measure 08/06/1982																																
Pumping Level (below land surface) 28 ft. 1 hrs. Pumping at 5 g.p.m.																																
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																
Grouting Information Well Grouted? ☐ Yes ☐ No ☐ Not Specified																																
Nearest Known Source of Contamination <u>50</u> feet <u>North</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No																																
Pump ☐ Not Installed Date Installed <u>08/07/1982</u> Manufacturer's name STA-RITE Model Number <u>SSJD</u> HP <u>0.75</u> Volt <u>230</u> Length of drop pipe <u>34</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>																																
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																
Angled Drill Hole																																
Well Contractor Nevis Well Drilling 29383 STEPHENSON, C Licensee Business Lic. or Reg. No. Name of Driller																																