

191060

County Hubbard
Quad Nevis
Quad ID 255A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/25/1990
Update Date 08/18/2016
Received Date

Well Name BAXTER, GREG	Township 140	Range 33	Dir Section W 9	Subsection CCDDAA	Well Depth 40 ft.	Depth Completed 40 ft.	Date Well Completed 05/11/1985																				
Elevation 1449	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Jetted	Drill Fluid																				
Address Well 24198 200TH ST NEVIS MN 56467					Use domestic	Status Active																					
Stratigraphy Information					Well Hydrofractured? Yes ☐ No ☐ From To																						
<table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND</td><td>0</td><td>30</td><td></td><td></td></tr><tr><td>HARDPAN</td><td>30</td><td>33</td><td>BROWN</td><td>HARD</td></tr><tr><td>COARSE GRAVEL</td><td>33</td><td>40</td><td></td><td></td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	SAND	0	30			HARDPAN	30	33	BROWN	HARD	COARSE GRAVEL	33	40			Casing Type Single casing Joint		
Geological Material	From	To (ft.)	Color	Hardness																							
SAND	0	30																									
HARDPAN	30	33	BROWN	HARD																							
COARSE GRAVEL	33	40																									
					Drive Shoe? Yes ☐ No ☐ Above/Below 1 ft.																						
					Open Hole <table><tr><td>From</td><td>ft.</td><td>To</td><td>ft.</td></tr><tr><td>Screen? ☒</td><td>Type galvanized</td><td>Make JOHNSON</td><td></td></tr><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td></tr><tr><td>1.2 in.</td><td>10</td><td>4 ft.</td><td>36 ft. 40 ft.</td></tr></table>			From	ft.	To	ft.	Screen? ☒	Type galvanized	Make JOHNSON		Diameter	Slot/Gauze	Length	Set	1.2 in.	10	4 ft.	36 ft. 40 ft.				
From	ft.	To	ft.																								
Screen? ☒	Type galvanized	Make JOHNSON																									
Diameter	Slot/Gauze	Length	Set																								
1.2 in.	10	4 ft.	36 ft. 40 ft.																								
					Static Water Level 15 ft. land surface Measure 05/11/1985																						
					Pumping Level (below land surface) 25 ft. 1 hrs. Pumping at 7 g.p.m.																						
					Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																						
					Grouting Information Well Grouted? ☐ Yes ☐ No ☐ Not Specified																						
					Nearest Known Source of Contamination 100 feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☐ Yes ☐ No																						
					Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																						
					Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																						
					Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																						
					Miscellaneous First Bedrock Aquifer Quat. Water Last Strat sand Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 357807 Y 5201414 Unique Number Verification Tax Records Input Date 03/18/2015																						
					Angled Drill Hole																						
					Well Contractor Nevis Well Drilling 29383 STEPHENSON, C Licensee Business Lic. or Reg. No. Name of Driller																						