

193782

County

Anoka

Quad

Coon Lake

Quad ID

135C

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

04/15/1991

Update Date

02/14/2014

Received Date

Well Name KORDIAK,					Township 33					Range 23					Dir Section W 19					Subsection ADAADA					Well Depth 87 ft.					Depth Completed 87 ft.					Date Well Completed 02/14/1984				
Elevation 910 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)										Drill Method Cable Tool					Drill Fluid																			
Address C/W 20222 POLK ST NE MN																				Use domestic					Status Active														
																				Well Hydrofractured? Yes ☐ No ☐					From To														
Stratigraphy Information																				Casing Type Single casing					Joint Threaded														
																				Drive Shoe? Yes ☒ No ☐					Above/Below 1.5 ft.														
Geological Material SAND																				From 0					To (ft.) 10					Color BROWN					Hardness SOFT				
SAND																				10					40					BLUE					SOFT				
WATERSAND																				40					50					BROWN					SOFT				
CLAY																				50					60					RED					SOFT				
ROCKS & GRAVEL																				60					70					BROWN					HARD				
CLAY																				70					77					BROWN					HARD				
WATER SAND																				77					87					BROWN					SOFT				
																				Open Hole From ft. To ft.																			
Screen? ☒																				Type stainless					Make JOHNSON														
Diameter 2 in.																				Slot/Gauze 10					Length 4 ft.					Set 83 ft.					87 ft.				
Static Water Level 20 ft.																				land surface					Measure					02/14/1984									
Pumping Level (below land surface) 40 ft.																				2 hrs.					Pumping at					20 g.p.m.									
Wellhead Completion Pitless adapter manufacturer																				WHITEWATER					Model SU4X5.5														
☐ Casing Protection																				☒ 12 in. above grade																			
☐ At-grade (Environmental Wells and Borings ONLY)																																							
Grouting Information Well Grouted?																				☐ Yes					☐ No					☒ Not Specified									
Nearest Known Source of Contamination 75 feet																				Northwes Direction					Septic tank/drain field Type														
Well disinfected upon completion?																				☒ Yes					☐ No														
Pump ☐ Not Installed																				Date Installed 02/26/1984																			
Manufacturer's name STA-RITE																																							
Model Number 8P4C025																				HP 0.5					Volt 230														
Length of drop pipe 36 ft																				Capacity 12 g.p.					Typ Submersible														
Abandoned Does property have any not in use and not sealed well(s)?																				☐ Yes					☐ No														
Variance Was a variance granted from the MDH for this well?																				☐ Yes					☐ No														
Miscellaneous First Bedrock																				Aquifer Quat. buried																			
Last Strat sand-brown																				Depth to Bedrock ft																			
Located by Minnesota Geological Survey																																							
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)																																							
System UTM - NAD83, Zone 15, Meters																				X 480608					Y 5020438														
Unique Number Verification Information from																				Input Date 01/01/1990																			
Angled Drill Hole																																							
Well Contractor Torgerson, Art & Son																				02203					TORGERSON, A.														
Licensee Business																				Lic. or Reg. No.					Name of Driller														
Minnesota Well Index Report										193782										Printed on 10/02/2026																			
																				HE-01205-15																			