

257010

County Sherburne
Quad Orrock
Quad ID 137B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/18/2006
Update Date 02/16/2012
Received Date

Well Name HANSON, STAN					Township 35	Range 27	Dir W	Section 25	Subsection AACACC	Well Depth 172 ft.		Depth Completed 172 ft.		Date Well Completed 06/11/1990																																																			
Elevation 988 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary		Drill Fluid																																																					
Address Well 14551 293RD AV NW ZIMMERMAN MN 55398										Use domestic		Status Unknown																																																					
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>COARSE SAND</td><td>0</td><td>65</td><td>DARK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>65</td><td>75</td><td>GRAY</td><td>HARD</td></tr><tr><td>CLAY</td><td>75</td><td>85</td><td>BROWN</td><td>HARD</td></tr><tr><td>CLAY</td><td>85</td><td>97</td><td>LT. TAN</td><td>HARD</td></tr><tr><td>CLAY</td><td>97</td><td>122</td><td>TAN</td><td>HARD</td></tr><tr><td>CLAY</td><td>122</td><td>127</td><td>TAN</td><td></td></tr><tr><td>SANDSTONE W/WHITE</td><td>127</td><td>147</td><td></td><td>MEDIUM</td></tr><tr><td>SANDSTONE W/WHITE</td><td>147</td><td>153</td><td></td><td>MEDIUM</td></tr><tr><td>DIORTE</td><td>153</td><td>172</td><td>GRAY</td><td>HARD</td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	COARSE SAND	0	65	DARK	SOFT	CLAY	65	75	GRAY	HARD	CLAY	75	85	BROWN	HARD	CLAY	85	97	LT. TAN	HARD	CLAY	97	122	TAN	HARD	CLAY	122	127	TAN		SANDSTONE W/WHITE	127	147		MEDIUM	SANDSTONE W/WHITE	147	153		MEDIUM	DIORTE	153	172	GRAY	HARD	Well Hydrofractured? Yes ☐ No ☐		From		To	
										Geological Material	From	To (ft.)	Color	Hardness																																																			
										COARSE SAND	0	65	DARK	SOFT																																																			
										CLAY	65	75	GRAY	HARD																																																			
										CLAY	75	85	BROWN	HARD																																																			
										CLAY	85	97	LT. TAN	HARD																																																			
										CLAY	97	122	TAN	HARD																																																			
										CLAY	122	127	TAN																																																				
										SANDSTONE W/WHITE	127	147		MEDIUM																																																			
										SANDSTONE W/WHITE	147	153		MEDIUM																																																			
DIORTE	153	172	GRAY	HARD																																																													
Casing Type										Joint																																																							
Drive Shoe?		Yes ☐		No ☐		Above/Below																																																											
Open Hole From _____ ft. To _____ ft.																																																																	
Screen? ☐		Type				Make																																																											
Static Water Level																																																																	
Pumping Level (below land surface)																																																																	
Wellhead Completion Pitless adapter manufacturer _____ Model _____ ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																																	
Grouting Information		Well Grouted?		☐ Yes ☐ No ☒ Not Specified																																																													
Nearest Known Source of Contamination _____ feet _____ Direction _____ Type _____ Well disinfected upon completion? ☐ Yes ☐ No																																																																	
Pump ☐ Not Installed		Date Installed																																																															
Manufacturer's name				Model Number		HP		Volt																																																									
Length of drop pipe				ft		Capacity		g.p.		Typ																																																							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																																																	
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																																																	
Miscellaneous First Bedrock Mt.Simon Sandstone Aquifer Last Strat Becker terrane-gran. Depth to Bedrock 122 ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 450184 Y 5038536 Unique Number Verification Information from Input Date 05/18/2006																																																																	
Angled Drill Hole																																																																	
Well Contractor A-well Co. 02484 WOLTERS, P. Licensee Business Lic. or Reg. No. Name of Driller																																																																	

Minnesota Well Index Report	257010	Printed on 10/02/2026 HE-01205-15
-----------------------------	--------	--------------------------------------