

405232

County Anoka
Quad Centerville
Quad ID 119A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/15/1991
Update Date 02/14/2014
Received Date

Well Name Township Range Dir Section Subsection 31 22 W 9 BCABCD					Well Depth 64 ft.		Depth Completed 64 ft.		Date Well Completed 11/23/1984	
Elevation 912 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Cable Tool		Drill Fluid			
Address C/W 859 LOIS LA MN					Use domestic		Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 42 GRAY SOFT CLAY 42 56 BLUE SOFT CLAY 56 60 RED SOFT SAND 60 64 BROWN SOFT					Well Hydrofractured? Yes ☐ No ☐		From To			
					Casing Type Single casing		Joint Threaded			
					Drive Shoe? Yes ☒ No ☐		Above/Below 1 ft.			
					Casing Diameter Weight					
					4 in. To 60 ft. 11 lbs./ft.					
					Open Hole From ft. To ft.					
					Screen? ☒ Type stainless		Make JOHNSON			
					Diameter Slot/Gauze Length Set					
					4 in. 12 5 ft. 60 ft. 64 ft.					
					Static Water Level					
21 ft. land surface		Measure		11/23/1984						
Pumping Level (below land surface)					35 ft. 2 hrs. Pumping at		20 g.p.m.			
Wellhead Completion					Pitless adapter manufacturer WHITEWATER Model SU4					
					☐ Casing Protection ☐ 12 in. above grade					
					☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified										
Nearest Known Source of Contamination					75 feet North Direction		Septic tank/drain field Type			
Well disinfected upon completion? ☒ Yes ☐ No										
Pump ☐ Not Installed Date Installed 11/15/1984					Manufacturer's name MYERS					
Model Number SJ HP 0.5 Volt 230					Length of drop pipe 40 ft Capacity 10 g.p. Typ Submersible					
Abandoned					Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No					
Variance					Was a variance granted from the MDH for this well? ☐ Yes ☐ No					
Miscellaneous					First Bedrock Aquifer Quat. buried					
Last Strat sand-brown Depth to Bedrock ft										
Located by Minnesota Geological Survey										
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)										
System UTM - NAD83, Zone 15, Meters X 492247 Y 5004285										
Unique Number Verification Address verification Input Date 01/01/1990										
Angled Drill Hole										
Well Contractor					Sampson Bros. Well 02088 BORN, L.					
Licensee Business Lic. or Reg. No. Name of Driller										
Remarks NORTH 0.5 SECT.										
Minnesota Well Index Report					405232				Printed on 08/13/2026 HE-01205-15	