

405233

County Anoka
Quad Centerville
Quad ID 119A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/15/1991
Update Date 02/14/2014
Received Date

Well Name SCHNEIDER	Township 31	Range 22	Dir W	Section 9	Subsection BDBDAB	Well Depth 58 ft.	Depth Completed 58 ft.	Date Well Completed 11/01/1984																				
Elevation 912 ft.	Elev. Method 7.5 minute topographic map (+/- 5 feet)	Drill Method Cable Tool Drill Fluid																										
Address C/W 939 LOIS LA MN						Use domestic Status Active																						
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☐ From To																						
<table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND</td><td>0</td><td>33</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>33</td><td>52</td><td>BLUE</td><td>SOFT</td></tr><tr><td>SAND</td><td>52</td><td>58</td><td>RED</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SAND	0	33	GRAY	SOFT	CLAY	33	52	BLUE	SOFT	SAND	52	58	RED	SOFT	Casing Type Single casing Joint Threaded		
Geological Material	From	To (ft.)	Color	Hardness																								
SAND	0	33	GRAY	SOFT																								
CLAY	33	52	BLUE	SOFT																								
SAND	52	58	RED	SOFT																								
Drive Shoe? Yes ☒ No ☐ Above/Below 1 ft.						Casing Diameter Weight																						
						4 in. To 54 ft. 11 lbs./ft.																						
Open Hole						From ft. To ft.																						
Screen? ☒ Type stainless Make JOHNSON						Diameter Slot/Gauze Length Set																						
4 in. 12 5 ft. 54 ft. 58 ft.																												
Static Water Level						20 ft. land surface Measure 11/01/1984																						
Pumping Level (below land surface)						37 ft. 2 hrs. Pumping at 25 g.p.m.																						
Wellhead Completion						Pitless adapter manufacturer MONITOR Model SNAPPY																						
☐ Casing Protection ☐ 12 in. above grade						☐ At-grade (Environmental Wells and Borings ONLY)																						
Grouting Information						Well Grouted? ☐ Yes ☒ No ☐ Not Specified																						
Nearest Known Source of Contamination						65 feet North Direction Septic tank/drain field Type																						
Well disinfected upon completion? ☒ Yes ☐ No																												
Pump ☐ Not Installed Date Installed 11/02/1984						Manufacturer's name PIONEER																						
Model Number A1012C HP 0.5 Volt 230						Length of drop pipe 40 ft Capacity 10 g.p. Typ Submersible																						
Abandoned						Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																						
Variance						Was a variance granted from the MDH for this well? ☐ Yes ☐ No																						
Miscellaneous						First Bedrock Aquifer Quat. buried																						
Last Strat sand-red Depth to Bedrock ft						Located by Minnesota Geological Survey																						
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)						System UTM - NAD83, Zone 15, Meters X 492562 Y 5004273																						
Unique Number Verification Information from Input Date 01/01/1990																												
Angled Drill Hole																												
Well Contractor						Sampson Bros. Well 02088 BORN, L.																						
Licensee Business Lic. or Reg. No. Name of Driller																												