

430263

County Anoka
Quad Nowthen
Quad ID 136C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/15/1991
Update Date 08/18/2014
Received Date

Well Name DANIELSON,					Township 33					Range 25					Dir Section W 33					Subsection ADDCAA					Well Depth 262 ft.					Depth Completed 262 ft.					Date Well Completed 03/20/1997														
Elevation 922 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary					Drill Fluid Bentonite																																		
Address C/W 7303 185TH AV NW ANOKA MN 55303																									Use domestic					Status Active																			
Well Hydrofractured? Yes ☐ No ☐																									From To																								
Casing Type Single casing																									Joint Threaded																								
Drive Shoe? Yes ☒ No ☐																									Above/Below 1 ft.																								
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 25 BROWN SOFT CLAY 25 63 GRAY SOFT CLAY & GRAVEL 63 83 BROWN MEDIUM SANDROCK & SHALE 83 94 GRY/GRN SOFT SHALE & SANDROCK 94 203 GRN/TAN MEDIUM SHALE & SANDROCK 203 262 GRN/WHT MEDIUM																									Casing Diameter 4 in. To 133 ft. 11 lbs./ft.					Weight 6.2 in. To 133 ft. 4 in. To 262 ft.					Hole Diameter 6.2 in. To 133 ft. 4 in. To 262 ft.														
Open Hole From 133 ft. To 262 ft.																																																	
Screen? ☐																									Type					Make																			
Static Water Level 15 ft. land surface Measure 03/20/1987																																																	
Pumping Level (below land surface) 100 ft. hrs. Pumping at 60 g.p.m.																																																	
Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																	
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To neat cement 0 ft. 30 ft. bentonite 30 ft. 133 ft.																																																	
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No																																																	
Pump ☐ Not Installed Date Installed 10/04/1988 Manufacturer's name RED JACKET Model Number 50CNICN9B HP 0.5 Volt 230 Length of drop pipe 40 ft Capacity 10 g.p. Typ Submersible																																																	
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																																	
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																																	
Miscellaneous First Bedrock Tunnel City Group Aquifer Tunnel City- Last Strat Wonewoc Sandstone Depth to Bedrock 83 ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 464575 Y 5017150 Unique Number Verification Information from Input Date 04/29/2002																																																	
Angled Drill Hole																																																	
Well Contractor Mork Well Co. 02133 LAWRENCE, R. Licensee Business Lic. or Reg. No. Name of Driller																																																	
Minnesota Well Index Report															430263										Printed on 08/13/2026 HE-01205-15																								