

450571

County Anoka
Quad Centerville
Quad ID 119A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/15/1991
Update Date 02/14/2014
Received Date

Well Name				Township	Range	Dir	Section	Subsection	Well Depth				Depth Completed				Date Well Completed			
				31	22	W	29	CDADBC	103 ft.				103 ft.				08/29/1988			
Elevation		897 ft.		Elev. Method		7.5 minute topographic map (+/- 5 feet)														
Address																				
Well 595 CHIPPEWA TR LINO LAKES MN																				
Stratigraphy Information																				
Geological Material				From	To (ft.)	Color	Hardness													
SAND				0	18															
CLAY				18	63															
GRAVEL				63	77															
GRAVEL & CLAY				77	93															
GRAVEL & SAND				93	103															
Use domestic Status Active																				
Well Hydrofractured? Yes ☐ No ☐ From To																				
Casing Type Single casing Joint Welded																				
Drive Shoe? Yes ☐ No ☒ Above/Below 1 ft.																				
Casing Diameter Weight Hole Diameter																				
4 in. To 100 ft. 1.5 lbs./ft. 7 in. To 100 ft.																				
4 in. To 103 ft.																				
Open Hole From ft. To ft.																				
Screen? ☒ Type stainless Make JOHNSON																				
Diameter Slot/Gauze Length Set																				
2.5 in. 18 6 ft. 97 ft. 103 ft.																				
Static Water Level																				
30 ft. land surface Measure 08/29/1988																				
Pumping Level (below land surface)																				
55 ft. 3 hrs. Pumping at 40 g.p.m.																				
Wellhead Completion																				
Pitless adapter manufacturer SNAPPY Model																				
☐ Casing Protection ☒ 12 in. above grade																				
☐ At-grade (Environmental Wells and Borings ONLY)																				
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																				
Material Amount From To																				
neat cement 2.5 Sacks 0 ft. 30 ft.																				
Nearest Known Source of Contamination																				
30 feet Southeast Direction Sewer Type																				
Well disinfected upon completion? ☒ Yes ☐ No																				
Pump ☐ Not Installed Date Installed 09/30/1988																				
Manufacturer's name STA RITE																				
Model Number 8P4C025 HP 0.5 Volt 230																				
Length of drop pipe 55 ft Capacity 15 g.p. Typ Submersible																				
Abandoned																				
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																				
Variance																				
Was a variance granted from the MDH for this well? ☐ Yes ☐ No																				
Miscellaneous																				
First Bedrock Aquifer Quat. buried																				
Last Strat sand +larger Depth to Bedrock ft																				
Located by Minnesota Geological Survey																				
Locate Method GPS SA Off (averaged) (15 meters)																				
System UTM - NAD83, Zone 15, Meters X 491126 Y 4998619																				
Unique Number Verification Address verification Input Date 02/08/2010																				
Angled Drill Hole																				
Well Contractor																				
Mccullough & Sons 82054 MCCULLOUGH, J																				
Licensee Business Lic. or Reg. No. Name of Driller																				
Minnesota Well Index Report									450571			Printed on 08/13/2026 HE-01205-15								