

458594

County Stearns
Quad Greenwald
Quad ID 159D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 11/18/1992
Update Date 03/10/2014
Received Date

Well Name SCHOENBORN, 124					Township 33		Range W 14		Dir Section CAB		Subsection CAB	
Elevation 1230					Elev. Method 7.5 minute topographic map (+/- 5 feet)							
Address C/W 33856 290TH ST MELROSE MN 56352												
Stratigraphy Information												
Geological Material		From	To (ft.)	Color	Hardness							
SAND		0	12	BROWN								
SANDY CLAY		12	39	BROWN								
SANDY CLAY		39	93	GRAY								
SANDY GRAVEL		93	126	BROWN								
SANDY CLAY		126	127	GRAY								
Well Depth 127 ft.												
Depth Completed 127 ft.												
Date Well Completed 02/07/1990												
Drill Method Non-specified Rotary												
Drill Fluid Revert												
Use irrigation												
Status Active												
Well Hydrofractured? Yes ☐ No ☐ From To												
Casing Type Single casing												
Joint												
Drive Shoe? Yes ☐ No ☒ Above/Below 1 ft.												
Casing Diameter 12 in. To 106 ft. lbs./ft.												
Weight												
Open Hole From ft. To ft.												
Screen? ☒ Slot/Gauze ☐ Type stainless ☐ Make JOHNSON												
Diameter 12 in. 120 20 ft. 106 ft. 126 ft.												
Length Set												
Static Water Level 16 ft. land surface Measure 02/07/1990												
Pumping Level (below land surface) 120 ft. hrs. Pumping at 700 g.p.m.												
Wellhead Completion Pitless adapter manufacturer Model												
☐ Casing Protection ☒ 12 in. above grade												
☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified												
Material bentonite 0 0 ft. 96 ft.												
Amount 0 0 ft. 96 ft.												
From 0 ft. 96 ft.												
To ft. ft.												
Nearest Known Source of Contamination feet Direction Type												
Well disinfected upon completion? ☐ Yes ☐ No												
Pump ☐ Not Installed Date Installed												
Manufacturer's name												
Model Number HP Q Volt												
Length of drop pipe ft Capacity g.p. Typ												
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No												
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No												
Miscellaneous First Bedrock Aquifer Quat. buried												
Last Strat clay+sand-gray Depth to Bedrock ft												
Located by Minnesota Geological Survey												
Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table)												
System UTM - NAD83, Zone 15, Meters X 359709 Y 5045510												
Unique Number Verification Information from Input Date 01/01/1990												
Angled Drill Hole												
Well Contractor Traut M.J. Well Co. 71536 JEFF/DAN												
Licensee Business Lic. or Reg. No. Name of Driller												