

Entry Date	12/17/1991
Update Date	04/18/2025
Received Date	08/19/1991

Well Name KRUEGER,	Township 108	Range 41	Dir W	Section 36	Subsection AAAADC						
Elevation 1511	Elev. Method 7.5 minute topographic map (+/- 5 feet)										
Address											
Contact RR 2 LOT 58 SLAYTON MN 56172											
Well SLAYTON MN 56172											
Stratigraphy Information											
Geological Material		From	To (ft.)	Color	Hardness						
LOAM		0	2	BLACK	SOFT						
CLAY		2	28	YELLOW	SOFT						
CLAY		28	65	BLU/GRY	MEDIUM						
CLAY/GRAVEL		65	73	BLUE	HARD						
CLAY		73	83	BLUE	HARD						
SAND COARSE		83	85	BLUE	MEDIUM						
CLAY		85	87	BLUE	SOFT						
SAND COARSE		87	89	BLUE	MEDIUM						
CLAY		89	113	BLUE	HARD						
SAND COARSE		113	114	BLUE	MEDIUM						
CLAY		114	137	BROWN	HARD						
SAND FINE		137	139	BLUE							
CLAY		139	360	BLUE	M.HARD						
SAND FINE		360	374	GREEN							
						Well Depth 374 ft.		Depth Completed 374 ft.		Date Well Completed 05/03/1991	
						Drill Method Non-specified Rotary		Drill Fluid Bentonite			
						Use domestic		Status Active			
						Well Hydrofractured?		Yes ☐		No ☐	
						Casing Type Single casing		Joint			
						Drive Shoe?		Yes ☐		No ☐	
						Casing Diameter 5 in. To		Weight 364 ft.		Hole Diameter 10 in. To 364 ft.	
						Open Hole		From ft.		To ft.	
						Screen? ☒		Type stainless		Make JOHNSON	
						Diameter		Slot/Gauze Length		Set	
						3 in.		12		374 ft.	
						Static Water Level					
						90 ft.		land surface		Measure 05/03/1991	
						Pumping Level (below land surface)					
200 ft.		4 hrs.		Pumping at 30 g.p.m.							
Wellhead Completion											
Pitless adapter manufacturer		WHITEWATER		Model							
☐ Casing Protection		☒ 12 in. above grade									
☐ At-grade (Environmental Wells and Borings ONLY)											
Grouting Information											
Well Grouted?		☒ Yes ☐ No ☐ Not Specified									
Material		Amount		From To							
neat cement		0		0 ft. 30 ft.							
bentonite		0		30 ft. 350 ft.							
Nearest Known Source of Contamination											
150 feet		North Direction		Sewer Type							
Well disinfected upon completion?		☒ Yes ☐ No									
Pump ☐		Not Installed		Date Installed 05/03/1991							
Manufacturer's name		JACUZZI									
Model Number		HP 1		Volt 230							
Length of drop pipe 300 ft		Capacity 12 g.p.		Type Submersible							
Abandoned											
Does property have any not in use and not sealed well(s)?		☐ Yes ☒ No									
Variance											
Was a variance granted from the MDH for this well?		☐ Yes ☐ No									
Miscellaneous											
First Bedrock		Cretaceous undiff.		Aquifer Cretaceous,							
Last Strat		Cretaceous undiff.		Depth to Bedrock 360 ft							
Located by		Minnesota Geological Survey									
Locate Method		Digitized - scale 1:24,000 or larger (Digitizing Table)									
System		UTM - NAD83, Zone 15, Meters		X 283674 Y 4889071							
Unique Number Verification		Information from		Input Date 01/01/1994							
Angled Drill Hole											
Well Contractor											
Steffl C.t. Well Co.		08044		STEFFL, C.							
Licensee Business		Lic. or Reg. No.		Name of Driller							

Minnesota Well Index Report	460994	Printed on 08/13/2026 HE-01205-15
------------------------------------	---------------	--------------------------------------