

483999

County Isanti
Quad Braham
Quad ID 152B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 11/28/1993
Update Date 06/03/2015
Received Date 10/27/1993

Well Name FORSLIN, DALE	Township 37	Range 23	Dir W	Section 16	Subsection CDCDBC
Elevation 966 ft.	Elev. Method LiDAR 1m DEM (MNDNR)				
Address Well 2045 397TH AV NE STANCHFIELD MN 55080					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
CLAY		0	6	BROWN	SOFT
CLAY		6	15	TAN	SOFT
CLAY		15	53	GRAY	SOFT
CLAY & GRAVEL		53	125	BROWN	MEDIUM
SAND		125	137	BROWN	SOFT

Well Depth 137 ft.	Depth Completed 137 ft.	Date Well Completed 03/07/1993
Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Use domestic	Status Active	
Well Hydrofractured? Yes ☐ No ☐	From	To
Casing Type Step down	Joint Threaded	
Drive Shoe? Yes ☐ No ☐	Above/Below	
Casing Diameter 4 in. To 132 ft. lbs./ft.		
Weight 4 in. To 7 ft. lbs./ft.		
Open Hole From ft. To ft.		
Screen? ☒	Type plastic	Make EVERFLO
Diameter 4 in.	Slot/Gauze Length 10 ft.	Set 132 ft. 137 ft.
Static Water Level 35 ft. land surface Measure 03/07/1993		
Pumping Level (below land surface) 120 ft. 1.5 hrs. Pumping at 40 g.p.m.		
Wellhead Completion Pitless adapter manufacturer MOINTOR Model SNAPPY		
☒ Casing Protection ☒ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)		
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material neat cement	Amount 5 Sacks	From 0 ft. 30 ft.
cuttings		To 30 ft. 132 ft.
Nearest Known Source of Contamination 63 feet North Direction Barnyard Type		
Well disinfected upon completion? ☒ Yes ☐ No		
Pump ☐ Not Installed Date Installed		
Manufacturer's name		
Model Number	HP	Volt
Length of drop pipe ft	Capacity g.p.	Typ
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No		
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No		
Miscellaneous First Bedrock Aquifer Quat. buried		
Last Strat sand-brown	Depth to Bedrock ft	
Located by Minnesota Geological Survey		
Locate Method GPS SA Off (averaged) (15 meters)		
System UTM - NAD83, Zone 15, Meters	X 483064	Y 5059426
Unique Number Verification	Address verification	Input Date 05/29/2014
Angled Drill Hole		
Well Contractor Mid-state Well 30604 LAWERENCE, R.		
Licensee Business Lic. or Reg. No. Name of Driller		

Remarks
OWNER AT TIME WELL DRILLED: JACOBS, WILFRED.