Minnesota Unique Well Number

485060

County Todd
Quad Long Prairie
Quad ID 178A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT

Entry Date 07/06/1993
Update Date 02/14/2014
Received Date

Well Name	Township	Range	Dir	Section	Subsection
ZINTER, DON	129	33	W	9	CDACBA

Elevation 1299 ft. **Elev. Method** 7.5 minute topographic map (+/- 5 feet)

Address

Well 25087 5 CR LONG PRAIRIE MN
Contact BOX 156 LONG PRAIRIE MN 56347

Stratigraphy Information

Geological Material	From	To (ft.)	Color	Hardness
SAND	0	43	BROWN	SOFT
CLAY	43	43	GRAY	MEDIUM

Remarks
USE-WASHING POTATOES AT PLANT OFFICE.

Well Depth 43 ft. **Depth Completed** 43 ft. **Date Well Completed** 07/28/1992

Drill Method Non-specified Rotary **Drill Fluid** Additive (+ Bentonite)

Use domestic **Status** Active

Well Hydrofractured? Yes ☐ No ☐ **From** **To**

Casing Type Single casing **Joint** Welded
Drive Shoe? Yes ☐ No ☒ **Above/Below**

Casing Diameter	Weight	Hole Diameter
8 in. To 33 ft.	lbs./ft.	14 in. To 43 ft.

Open Hole From ft. To ft.

Screen? ☒ **Type** stainless **Make** JOHNSON

Diameter	Slot/Gauze	Length	Set Between
8 in.	90	10 ft.	33 ft. 43 ft.

Static Water Level
19 ft. land surface Measure Date 07/28/1992

Pumping Level (below land surface)
30 ft. after 3 hrs. Pumping at 80 g.p.m.

Wellhead Completion
Pitless adapter manufacturer Model
☐ Casing Protection ☒ 12 in. above grade
☐ At-grade (Environmental Wells and Borings ONLY)

Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified

Material	Amount	From	To
bentonite		0 ft.	30 ft.

Nearest Known Source of Contamination
feet Direction Type
Well disinfected upon completion? ☒ Yes ☐ No

Pump ☐ Not Installed Date Installed 07/30/1992
Manufacturer's name GRUNDFOS
Model Number 135S75-4 HP 7.5 Volt 230
Length of drop pipe 35 ft Capacity 50 g.p.m. Type Submersible

Abandoned Wells
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No

Variance
Was a variance granted from the MDH for this well? ☐ Yes ☐ No

Miscellaneous
First Bedrock Aquifer Quat. Water Table
Last Strat clay-gray Depth to Bedrock ft.
Located by Minnesota Geological Survey
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or better)
System UTM - NAD83, Zone 15, Meters X 356937 Y 5095002
Unique Number Verification Information from Input Date 12/03/2003

Angled Drill Hole

Well Contractor Certification
Traut S.M. Well Co. 21535 NEYENS, J.
Licensee Business Name Lic. or Reg. No. Name of Driller