

486191

County Anoka
Quad Nowthen
Quad ID 136C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 12/13/1991
Update Date 02/14/2014
Received Date 07/29/1991

Well Name 32 25 W 11 BDABDA					Well Depth 77 ft.		Depth Completed 77 ft.		Date Well Completed 07/15/1991			
Elevation 885 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary		Drill Fluid Bentonite					
Address C/W 17030 POTASSIUM ST NW RAMSEY MN					Use domestic		Status Active					
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 28 BROWN SOFT SANDY CLAY & 28 47 BROWN MEDIUM CLAY 47 54 BROWN MEDIUM GRAVEL 54 77 SOFT					Well Hydrofractured? Yes ☐ No ☐		From		To			
					Casing Type Single casing		Joint					
					Drive Shoe? Yes ☐ No ☐		Above/Below					
					Casing Diameter		Weight		Hole Diameter			
					4 in. To 67 ft.		lbs./ft.		8 in. To 30 ft. 6.7 in. To 77 ft.			
					Open Hole		From ft.		To ft.			
					Screen? ☒		Type stainless		Make JOHNSON			
					Diameter Slot/Gauze Length Set							
					2 in. 12 12 ft. 67 ft. 77 ft.							
					Static Water Level		20 ft. land surface		Measure		07/15/1991	
Pumping Level (below land surface)					62 ft. 0.5 hrs. Pumping at		40 g.p.m.					
Wellhead Completion					Pitless adapter manufacturer MONITOR		Model BULLDOG					
					☐ Casing Protection ☐ 12 in. above grade							
					☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information					Well Grouted? ☒ Yes ☐ No ☐ Not Specified							
Material Amount From To					neat cement		ft. 30 ft.					
Nearest Known Source of Contamination					feet Direction				Type			
Well disinfected upon completion? ☒ Yes ☐ No												
Pump ☐ Not Installed					Date Installed		07/18/1991					
Manufacturer's name MYERS												
Model Number S3N52-N510 HP 0.5					Volt 230							
Length of drop pipe 40 ft Capacity 10 g.p.					Typ Submersible							
Abandoned					Does property have any not in use and not sealed well(s)?		☐ Yes ☒ No					
Variance					Was a variance granted from the MDH for this well?		☐ Yes ☐ No					
Miscellaneous					First Bedrock		Aquifer Quat. buried					
Last Strat gravel (+larger)					Depth to Bedrock		ft					
Located by Minnesota Geological Survey												
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or												
System UTM - NAD83, Zone 15, Meters X 467009 Y 5014184												
Unique Number Verification Address verification Input Date 01/04/2010												
Angled Drill Hole												
Well Contractor					Mork Well Co. 02133		JENSEN, G.					
Licensee Business					Lic. or Reg. No.		Name of Driller					
Remarks												