

488491

County Isanti
Quad Wyanett
Quad ID 153C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/19/1991
Update Date 08/21/2014
Received Date 09/23/1991

Well Name GOETZE, DEAN	Township 36	Range 25	Dir Section W 35	Subsection AACBDD	Well Depth 70 ft.	Depth Completed 70 ft.	Date Well Completed 09/11/1991
Elevation 951 ft.	Elev. Method LiDAR 1m DEM (MNDNR)	Drill Method Non-specified Rotary				Drill Fluid Bentonite	
Address C/W 33163 HELIUM ST CAMBRIDGE MN 55008					Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 30 YELLOW SOFT CLAY 30 60 BLUE SOFT SAND 60 70 GRAY SOFT					Well Hydrofractured? Yes ☐ No ☐ From To		
					Casing Type Single casing Joint Glued		
					Drive Shoe? Yes ☐ No ☐ Above/Below 1 ft.		
					Hole Diameter 8 in. To 30 ft. 6.7 in. To 70 ft.		
					Open Hole From ft. To ft.		
					Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 2 in. 12 7 ft. 64 ft. 70 ft.		
					Static Water Level 42 ft. land surface Measure 09/19/1991		
					Pumping Level (below land surface) 32 ft. 1.5 hrs. Pumping at 14 g.p.m.		
					Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY ☒ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
					Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To neat cement 0 ft. 30 ft.		
Nearest Known Source of Contamination <u>51</u> feet <u>Northeas</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No							
Pump ☐ Not Installed Date Installed <u>09/11/1919</u> Manufacturer's name MEYERS Model Number <u>B52BM</u> HP <u>0.5</u> Volt <u>230</u> Length of drop pipe <u>50</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>							
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No							
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 467743 Y 5046335 Unique Number Verification Address verification Input Date 07/22/2014							
Angled Drill Hole							
Well Contractor Jim's Well Co. 60312 LOHSE, J. Licensee Business Lic. or Reg. No. Name of Driller							