

493938

County Carver
Quad Watertown
Quad ID 106A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/16/1992
Update Date 02/14/2014
Received Date

Well Name GREER,	Township 116	Range 25	Dir W	Section 3	Subsection ADCDC A	Well Depth 183 ft.	Depth Completed 183 ft.	Date Well Completed 01/21/1992
Elevation 1030	Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary	Drill Fluid	
Address						Use domestic	Status Active	
Well 11325 66TH ST WACONIA MN 55387						Well Hydrofractured? Yes ☐ No ☐ From To		
Contact 6305 TETON LA EXCELSIOR MN 55331						Casing Type Single casing Joint		
Stratigraphy Information						Drive Shoe? Yes ☒ No ☐ Above/Below 0 ft.		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
CLAY		0	168			4 in. To 179 ft. 10.86 lbs./ft. 6 in. To 183 ft.		
SAND		168	183					
Open Hole						From	ft.	To ft.
Screen? ☒						Type stainless	Make JOHNSON	
Diameter						Slot/Gauze	Length	Set
4 in.						10	4 ft.	179 ft. 183 ft.
Static Water Level								
120 ft.						land surface	Measure	01/21/1992
Pumping Level (below land surface)								
120 ft.						4 hrs.	Pumping at	20 g.p.m.
Wellhead Completion								
Pitless adapter manufacturer						WHITEWATER	Model	
☐ Casing Protection						☒ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material						Amount	From	To
cuttings						0	0 ft.	ft.
Nearest Known Source of Contamination								
feet						Direction	Type	
Well disinfected upon completion?						☐ Yes ☐ No		
Pump ☐ Not Installed						Date Installed	02/05/1992	
Manufacturer's name						MYERS		
Model Number						HP 1	Volt	230
Length of drop pipe						147 ft	Capacity	14 g.p. Typ Submersible
Abandoned								
Does property have any not in use and not sealed well(s)?						☐ Yes ☒ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☐ No		
Miscellaneous								
First Bedrock						Aquifer	Quat. buried	
Last Strat sand						Depth to Bedrock	ft	
Located by						Minnesota Geological Survey		
Locate Method						Digitized - scale 1:24,000 or larger (Digitizing Table)		
System						UTM - NAD83, Zone 15, Meters	X 435886	Y 4970381
Unique Number Verification						Address verification	Input Date	03/02/1995
Angled Drill Hole								
Well Contractor								
Stodola Don Well Co.						27172	HIGH, W.	
Licensee Business						Lic. or Reg. No.	Name of Driller	