

504720

County Stearns
Quad Little Rock
Quad ID 156B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/03/1991
Update Date 02/14/2014
Received Date

Well Name TRAUT, ROD					Township 125	Range 28	Dir W	Section 4	Subsection ABABAB	Well Depth 72 ft.				Depth Completed 72 ft.				Date Well Completed 06/02/1989																																			
Elevation 1039					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary				Drill Fluid Revert																																							
Address C/W 37997 1 CR MN										Use domestic				Status Active																																							
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND & GRAVEL</td><td>0</td><td>28</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SILTY SAND</td><td>28</td><td>41</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND & GRAVEL</td><td>41</td><td>43</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>43</td><td>50</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SILTY SAND</td><td>50</td><td>66</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND & GRAVEL</td><td>66</td><td>72</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>72</td><td>72</td><td>GRAY</td><td>SOFT</td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	SAND & GRAVEL	0	28	BROWN	SOFT	SILTY SAND	28	41	BROWN	SOFT	SAND & GRAVEL	41	43	BROWN	SOFT	SANDY CLAY	43	50	BROWN	SOFT	SILTY SAND	50	66	BROWN	SOFT	SAND & GRAVEL	66	72	GRAY	SOFT	SANDY CLAY	72	72	GRAY	SOFT	Well Hydrofractured? Yes ☐ No ☐ From To			
										Geological Material	From	To (ft.)	Color	Hardness																																							
										SAND & GRAVEL	0	28	BROWN	SOFT																																							
										SILTY SAND	28	41	BROWN	SOFT																																							
										SAND & GRAVEL	41	43	BROWN	SOFT																																							
										SANDY CLAY	43	50	BROWN	SOFT																																							
										SILTY SAND	50	66	BROWN	SOFT																																							
										SAND & GRAVEL	66	72	GRAY	SOFT																																							
										SANDY CLAY	72	72	GRAY	SOFT																																							
										Casing Type Single casing				Joint Glued																																							
Drive Shoe? Yes ☐ No ☐ Above/Below 0 ft.																																																					
Casing Diameter 4 in.				Weight To 68 ft. lbs./ft.																																																	
Open Hole From ft. To ft.																																																					
Screen? ☒ Type stainless Make JOHNSON																																																					
Diameter Slot/Gauze Length Set																																																					
4 in. 20 4 ft. 68 ft. 72 ft.																																																					
Static Water Level 16 ft. land surface Measure 06/02/1989																																																					
Pumping Level (below land surface) 70 ft. hrs. Pumping at 50 g.p.m.																																																					
Wellhead Completion Pitless adapter manufacturer MAAS Model 4JL ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To neat cement 0 7 ft. 37 ft.																																																					
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☐ Yes ☐ No																																																					
Pump ☐ Not Installed Date Installed 06/15/1989 Manufacturer's name AERMOTOR Model Number A12B50 HP 0.5 Volt 230 Length of drop pipe 30 ft Capacity 12 g.p. Typ Submersible																																																					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																																					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																																					
Miscellaneous First Bedrock Aquifer Quat. Water Last Strat clay+sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table) System UTM - NAD83, Zone 15, Meters X 405882 Y 5058513 Unique Number Verification Information from Input Date 01/01/1990																																																					
Angled Drill Hole																																																					
Well Contractor Traut M.J. Well Co. 71536 BRUCE/MARK Licensee Business Lic. or Reg. No. Name of Driller																																																					

Minnesota Well Index Report	504720	Printed on 10/02/2026 HE-01205-15
-----------------------------	--------	--------------------------------------