

508831

County

Blue Earth

Quad

Beauford

Quad ID

55C

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

06/17/1997

Update Date

03/03/2017

Received Date

Well Name MAY, GENE Township 107 Range 26 Dir Section W 36 Subsection ADAADB	Well Depth 104 ft. Depth Completed 104 ft. Date Well Completed 07/25/1991																																			
Elevation 1012 Elev. Method 7.5 minute topographic map (+/- 5 feet)	Drill Method Cable Tool Drill Fluid Bentonite																																			
Address ContactRR 4 BOX 122 MANKATO MN 56001	Use domestic Status Sealed																																			
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>3</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>3</td><td>20</td><td>YELLOW</td><td>SOFT</td></tr><tr><td>CLAY</td><td>20</td><td>60</td><td>BLUE</td><td>SOFT</td></tr><tr><td>SAND</td><td>60</td><td>62</td><td>GRAY</td><td>HARD</td></tr><tr><td>CLAY</td><td>62</td><td>85</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>85</td><td>104</td><td>GRAY</td><td>SOFT</td></tr></table>	Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	3	BLACK	SOFT	CLAY	3	20	YELLOW	SOFT	CLAY	20	60	BLUE	SOFT	SAND	60	62	GRAY	HARD	CLAY	62	85	GRAY	SOFT	SAND	85	104	GRAY	SOFT	Well Hydrofractured? Yes☐ No☐ From To Casing Type Single casing Joint Threaded
	Geological Material	From	To (ft.)	Color	Hardness																															
	TOP SOIL	0	3	BLACK	SOFT																															
	CLAY	3	20	YELLOW	SOFT																															
	CLAY	20	60	BLUE	SOFT																															
	SAND	60	62	GRAY	HARD																															
	CLAY	62	85	GRAY	SOFT																															
	SAND	85	104	GRAY	SOFT																															
	Drive Shoe? Yes☒ No☐ Above/Below 2 ft.	Casing Diameter 5 in. Weight 100 ft. Hole Diameter 5 in. 104 ft.																																		
	Open Hole From ft. To ft.	Screen? ☒ Type stainless Make JOHNSON																																		
Diameter 4 in. Slot/Gauze 12 Length 5 ft. Set 100 ft. 104 ft.																																				
Static Water Level 35 ft. land surface Measure 07/23/1991																																				
Pumping Level (below land surface) 60 ft. 10 hrs. Pumping at 30 g.p.m.																																				
Wellhead Completion Pitless adapter manufacturer MONITOR Model 6PS56 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																				
Grouting Information Well Grouted? ☐ Yes ☒ No ☐ Not Specified																																				
Nearest Known Source of Contamination 100 feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☐ Yes ☐ No																																				
Pump ☐ Not Installed Date Installed 07/25/1991 Manufacturer's name GOULDS Model Number 10EJ07 HP 0.75 Volt 230																																				
Length of drop pipe 60 ft Capacity 15 g.p. Typ Submersible																																				
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																				
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																				
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft																																				
Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 428765 Y 4875849																																				
Unique Number Verification Name on mailbox Input Date 04/14/2009																																				
Angled Drill Hole																																				
Well Contractor Denn Well Co. 07120 DENN, L. Licensee Business Lic. or Reg. No. Name of Driller																																				
Minnesota Well Index Report	508831	Printed on 10/02/2026 HE-01205-15																																		