

514961

County Stearns
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/27/1993
Update Date 02/14/2014
Received Date

Well Name VERHOEFF,	Township 123	Range 34	Dir W	Section 30	Subsection DBB	Well Depth 125 ft.	Depth Completed 125 ft.	Date Well Completed 10/23/1992
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Well 21602 71 HY BELGRADE MN 56312						Well Hydrofractured? Yes ☐ No ☐ From To		
Contact 43184 FOXBORO RD BELGRADE MN 56312						Casing Type Single casing Joint Glued		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☐ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
TOPSOIL		0	1			4 in. To 120 ft. lbs./ft. 4 in. To 125 ft.		
SAND/GRAVEL		1	33					
CLAY		33	73	GRAY	M.SOFT			
CLAY		73	95	GRAY	M.HARD			
CLAY		95	115	YELLOW	M.SOFT			
SAND/GRAVEL		115	125					
Open Hole						From	ft.	To ft.
Screen? ☒						Type plastic	Make CERTA-LOK	
Diameter						Slot/Gauze	Length	Set
4 in.						18	5 ft.	120 ft. 125 ft.
Static Water Level								
15 ft.						land surface	Measure	10/23/1992
Pumping Level (below land surface)								
30 ft.						12 hrs.	Pumping at	18 g.p.m.
Wellhead Completion								
Pitless adapter manufacturer						Model		
☐ Casing Protection						☐ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material				Amount		From	To	
neat cement						0	ft. 30	ft.
cuttings						30	ft. 115	ft.
other						115	ft. 125	ft.
Nearest Known Source of Contamination								
feet						Direction	Type	
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☐ Not Installed						Date Installed		
Manufacturer's name								
Model Number				HP		Volt		
Length of drop pipe				ft	Capacity	g.p.	Typ	
Abandoned								
Does property have any not in use and not sealed well(s)?						☐ Yes ☒ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☐ No		
Miscellaneous								
First Bedrock						Aquifer		
Last Strat						Depth to Bedrock ft		
Located by								
Locate Method								
System UTM - NAD83, Zone 15, Meters				X		Y		
Unique Number Verification						Input Date		
Angled Drill Hole								
Well Contractor								
Blue Water Well Co.						73413	ALFORD, M	
Licensee Business						Lic. or Reg. No.	Name of Driller	
Remarks								
GROUTING MATERIAL: GRAVEL PACK 115-125								
Minnesota Well Index Report						514961		
						Printed on 08/13/2026 HE-01205-15		