

515630

County Polk
Quad Fosston SE
Quad ID 332D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/03/1995
Update Date 05/11/2021
Received Date 09/16/1994

Well Name TRUSCINSKI,	Township 147	Range 39	Dir W	Section 34	Subsection BBBDBD	Well Depth 78 ft.	Depth Completed 78 ft.	Date Well Completed 06/25/1994
Elevation 1432	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Contact RR 1 BOX 1805 LENGBY MN 56651						Well Hydrofractured? Yes ☐ No ☐ From To		
Well RR 1 LENGBY MN						Casing Type Single casing Joint		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☐ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
CLAY		0	20	YELLOW	MEDIUM	4 in. To 74 ft. lbs./ft. 9 in. To 30 ft.		
CLAY		20	35	BROWN	MEDIUM	6.7 in. To 78 ft.		
GRAVEL		35	78	YELLOW	MEDIUM			
Open Hole						From	ft.	To ft.
Screen? ☒						Type stainless	Make COOK	
Diameter Slot/Gauze						Length	Set	
2 in. 18						4 ft. 74	ft. 78	ft.
Static Water Level								
52 ft. land surface						Measure	06/25/1994	
Pumping Level (below land surface)								
68 ft. 2 hrs. Pumping at						30	g.p.m.	
Wellhead Completion								
Pitless adapter manufacturer MAASS Model 4JC1								
☐ Casing Protection ☒ 12 in. above grade								
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material Amount From To								
bentonite 2 Sacks 8 ft. 30 ft.								
Nearest Known Source of Contamination								
85 feet Northwes Direction						Septic tank/drain field Type		
Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed 06/25/1994								
Manufacturer's name AERMOTOR								
Model Number A12B50 HP 0.5 Volt 230								
Length of drop pipe 60 ft Capacity 12 g.p. Typ Submersible								
Abandoned								
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance								
Was a variance granted from the MDH for this well? ☐ Yes ☐ No								
Miscellaneous								
First Bedrock						Aquifer	Quat. buried	
Last Strat gravel (+larger)-yellow						Depth to Bedrock	ft	
Located by Minnesota Geological Survey								
Locate Method GPS SA Off (averaged) (15 meters)								
System UTM - NAD83, Zone 15, Meters X 303003 Y 5265474								
Unique Number Verification Tax Records						Input Date	02/04/2020	
Angled Drill Hole								
Well Contractor								
Brovold Wells 60638 BROULD, K.								
Licensee Business						Lic. or Reg. No.	Name of Driller	
Remarks								
Minnesota Well Index Report						515630		
						Printed on 10/02/2026 HE-01205-15		