

517891

County Anoka
Quad Cedar
Quad ID 136D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 12/16/1993
Update Date 08/18/2014
Received Date 06/04/1993

Well Name 32 Well Depth 141 ft.					Township 24 Depth Completed 141 ft.					Range 24 Date Well Completed 04/21/1993				
Dir W Section 5 Elevation 899 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Subsection DDDDBDA					Drill Method Non-specified Rotary Drill Fluid Bentonite				
Address Well 3232 174TH AV NW ANDOVER MN														
Use domestic Status Active														
Well Hydrofractured? Yes ☐ No ☐ From To														
Casing Type Single casing Joint Threaded														
Drive Shoe? Yes ☒ No ☐ Above/Below														
Casing Diameter Weight Hole Diameter 4 in. To 89 ft. 20 lbs./ft. 3.8 in. To 89 ft. 6.1 in. To 141 ft.														
Open Hole From 89 ft. To 141 ft.														
Screen? ☐ Type Make														
Static Water Level 25 ft. land surface Measure 04/21/1993														
Pumping Level (below land surface)														
Wellhead Completion Pitless adapter manufacturer WHITEWATER Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)														
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite ft. 89 ft. cuttings ft. 89 ft.														
Nearest Known Source of Contamination feet Southeast Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No														
Pump ☐ Not Installed Date Installed 05/06/1993 Manufacturer's name MYERS Model Number HP 0.5 Volt 220 Length of drop pipe 40 ft Capacity 12 g.p. Typ Submersible														
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No														
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No														
Miscellaneous First Bedrock St.Lawrence-Tunnel City Aquifer St.Lawrence- Last Strat St.Lawrence-Tunnel City Depth to Bedrock 87 ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 472695 Y 5014738 Unique Number Verification Address verification Input Date 01/04/2010														
Angled Drill Hole														
Well Contractor Ruppert & Son 27086 RUPPERT, T Licensee Business Lic. or Reg. No. Name of Driller														
Minnesota Well Index Report					517891					Printed on 08/13/2026 HE-01205-15				