

522766

County Benton
Quad Foley
Quad ID 155B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/19/1993
Update Date 03/10/2014
Received Date

Well Name BRUA, JERRY					Township 37		Range 29		Dir Section W 24		Subsection BDDBBC																																													
Elevation 1145		Elev. Method 7.5 minute topographic map (+/- 5 feet)																																																						
Address Contact BOX 65 FOLEY MN 56329 Well 12890 JONQUIL RD FOLEY MN 56329																																																								
Stratigraphy Information <table><thead><tr><th>Geological Material</th><th>From</th><th>To (ft.)</th><th>Color</th><th>Hardness</th></tr></thead><tbody><tr><td>SANDY CLAY</td><td>0</td><td>14</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>14</td><td>50</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>50</td><td>51</td><td>GRAY</td><td>SOFT</td></tr><tr><td>GRANITE</td><td>51</td><td>58</td><td>PNK/WHT</td><td>MEDIUM</td></tr><tr><td>GRANITE</td><td>58</td><td>64</td><td>PNK/GRY</td><td>M.SOFT</td></tr><tr><td>GRANITE</td><td>64</td><td>157</td><td>PNK/BLK</td><td>M.HARD</td></tr><tr><td>GRANITE</td><td>157</td><td>163</td><td>PNK/BLK</td><td>M.SOFT</td></tr><tr><td>GRANITE</td><td>163</td><td>178</td><td>PNK/BLK</td><td>M.HARD</td></tr></tbody></table>												Geological Material	From	To (ft.)	Color	Hardness	SANDY CLAY	0	14	BROWN	SOFT	SANDY CLAY	14	50	GRAY	SOFT	SANDY CLAY	50	51	GRAY	SOFT	GRANITE	51	58	PNK/WHT	MEDIUM	GRANITE	58	64	PNK/GRY	M.SOFT	GRANITE	64	157	PNK/BLK	M.HARD	GRANITE	157	163	PNK/BLK	M.SOFT	GRANITE	163	178	PNK/BLK	M.HARD
Geological Material	From	To (ft.)	Color	Hardness																																																				
SANDY CLAY	0	14	BROWN	SOFT																																																				
SANDY CLAY	14	50	GRAY	SOFT																																																				
SANDY CLAY	50	51	GRAY	SOFT																																																				
GRANITE	51	58	PNK/WHT	MEDIUM																																																				
GRANITE	58	64	PNK/GRY	M.SOFT																																																				
GRANITE	64	157	PNK/BLK	M.HARD																																																				
GRANITE	157	163	PNK/BLK	M.SOFT																																																				
GRANITE	163	178	PNK/BLK	M.HARD																																																				
Well Depth 178 ft.		Depth Completed 178 ft.		Date Well Completed 12/14/1992																																																				
Drill Method Non-specified Rotary		Drill Fluid Additive (+ Bentonite)																																																						
Use domestic		Status Active																																																						
Well Hydrofractured? Yes ☐ No ☐		From To																																																						
Casing Type Single casing		Joint Threaded																																																						
Drive Shoe? Yes ☐ No ☐		Above/Below 0 ft.																																																						
Casing Diameter 6 in. To 52 ft.		Weight lbs./ft.		Hole Diameter 10 in. To 52 ft.		6 in. To 178 ft.																																																		
Open Hole From 52 ft. To 178 ft.																																																								
Screen? ☐		Type Make																																																						
Static Water Level 8 ft. land surface Measure 12/15/1992																																																								
Pumping Level (below land surface) 175 ft. 0.2 hrs. Pumping at 0.01 g.p.m.																																																								
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																								
Grouting Information Material Amount From To neat cement 0 7 ft. 52 ft.		Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																																						
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No																																																								
Pump Manufacturer's name Model Number HP Q Volt Length of drop pipe ft Capacity g.p. Typ		☐ Not Installed Date Installed																																																						
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No																																																								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																																								
Miscellaneous First Bedrock Foley Granite Aquifer Foley Granite Last Strat Foley Granite Depth to Bedrock 50 ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 430189 Y 5059564 Unique Number Verification Information from Input Date 07/10/2002																																																								
Angled Drill Hole																																																								
Well Contractor Traut M.J. Well Co. 71536 BRUCE/ROB Licensee Business Lic. or Reg. No. Name of Driller																																																								
Minnesota Well Index Report				522766		Printed on 10/02/2026 HE-01205-15																																																		