

529417

County Faribault
Quad Huntley
Quad ID 13B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/23/1995
Update Date 03/30/2020
Received Date

Well Name HANNAMAN, ED 102					Township 28	Range W 18	Dir Section BDBDBB	Well Depth 85 ft.					Depth Completed 85 ft.					Date Well Completed 06/30/1994											
Elevation 1109					Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary					Drill Fluid Bentonite														
Address C/W RR 1 BOX 108 BLUE EARTH MN										Use domestic					Status														
										Well Hydrofractured? Yes ☐ No ☐					From To														
Stratigraphy Information										Casing Type Single casing					Joint														
										Drive Shoe? Yes ☐ No ☐					Above/Below														
Geological Material										Casing Diameter					Weight														
DIRT										5 in. To					80 ft. lbs./ft.														
CLAY										2					20														
CLAY										20					65														
ROCK										65					66														
SAND										66					85														
										Open Hole					From ft. To ft.														
										Screen? ☒					Type telescoping					Make JOHNSON									
										Diameter					Slot/Gauze					Length Set									
										5 in.					20					5 ft. 80 ft. 85 ft.									
										Static Water Level																			
										10 ft.					land surface					Measure 06/30/1994									
										Pumping Level (below land surface)																			
										10 ft.					2 hrs.					Pumping at 60 g.p.m.									
										Wellhead Completion																			
										Pitless adapter manufacturer					MASS					Model J5.25									
										☐ Casing Protection					☐ 12 in. above grade														
										☐ At-grade (Environmental Wells and Borings ONLY)																			
										Grouting Information										Well Grouted? ☒ Yes ☐ No ☐ Not Specified									
										Nearest Known Source of Contamination																			
										40 feet					South Direction					Septic tank/drain field Type									
										Well disinfected upon completion? ☒ Yes ☐ No																			
										Pump ☐ Not Installed										Date Installed									
										Manufacturer's name										GOULDS									
										Model Number					10LSO5					HP 0.5					Volt 230				
										Length of drop pipe					60 ft					Capacity 10 g.p.					Typ Submersible				
										Abandoned																			
										Does property have any not in use and not sealed well(s)?										☐ Yes ☒ No									
										Variance																			
										Was a variance granted from the MDH for this well?										☐ Yes ☐ No									
										Miscellaneous																			
										First Bedrock					Aquifer					Quat. buried									
										Last Strat					sand-brown					Depth to Bedrock					ft				
										Located by										Minnesota Geological Survey									
										Locate Method										GPS SA Off (averaged) (15 meters)									
										System					UTM - NAD83, Zone 15, Meters					X 399857					Y 4832659				
										Unique Number Verification					Information from					Input Date					03/18/2020				
										Angled Drill Hole																			
										Well Contractor																			
										Garlick-ziemann					46489					KOESTLER, E.									
										Licensee Business					Lic. or Reg. No.					Name of Driller									