

529586

County Freeborn
Quad Albert Lea
Quad ID 10B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/04/1994
Update Date 11/28/2023
Received Date

Well Name LEVINE, PAUL						Township 103		Range 21		Dir Section W 7		Subsection ABBDCB		Well Depth 240 ft.				Depth Completed 240 ft.				Date Well Completed 10/13/1993			
Elevation 1293						Elev. Method LiDAR 1m DEM (MNDNR)												Drill Method Non-specified Rotary				Drill Fluid Bentonite			
Address Well 73476 270th ST Albert Lea MN Contact RR 2 BOX 189 ALBERT LEA MN 56007														Use domestic				Status Active							
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 180 BROWN SOFT SHALE 180 189 TAN SOFT SHALE 189 210 TAN HARD SHALE & LIMESTONE 210 220 BROWN HARD SHALE & LIMESTONE 220 230 BLUE HARD LIMESTONE 230 240 BROWN HARD														Well Hydrofractured? Yes ☐ No ☐				From To							
Casing Type Single casing														Joint Welded											
Drive Shoe? Yes ☒ No ☐														Above/Below											
Casing Diameter 5 in. To 200 ft.														Weight 15 lbs./ft.				Hole Diameter 8 in. To 200 ft. 5 in. To 240 ft.							
Open Hole From 200 ft. To 240 ft.																									
Screen? ☐														Type				Make							
Static Water Level 93 ft. land surface Measure 10/13/1993																									
Pumping Level (below land surface) 95 ft. hrs. Pumping at 40 g.p.m.																									
Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																									
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 3 Sacks 0 ft. 30 ft.																									
Nearest Known Source of Contamination 70 feet South Direction Other Type Well disinfected upon completion? ☒ Yes ☐ No																									
Pump ☐ Not Installed Date Installed 10/20/1993 Manufacturer's name MEYERS Model Number HP 0.5 Volt 230 Length of drop pipe 120 ft Capacity 10 g.p. Typ Submersible																									
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																									
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock 180 ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 467992 Y 4843541 Unique Number Verification Tax Records Input Date 02/24/2023																									
Angled Drill Hole																									
Well Contractor Morrison Well Co. 24001 MORRISON, G. Licensee Business Lic. or Reg. No. Name of Driller																									
Remarks 'STOCKYARD' IS POLLUTION SOURCE.																									