

535895

County Sherburne
Quad Lake
Quad ID 137A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/26/1994
Update Date 02/14/2014
Received Date

Well Name FOLLON,					Township 34	Range 26	Dir W	Section 26	Subsection CBBACB	Well Depth 330 ft.					Depth Completed 330 ft.					Date Well Completed 10/28/1993									
Elevation 1064					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary															Drill Fluid Bentonite				
Address Well 24015 112TH ST ZIMMERMAN MN										Use domestic															Status Active				
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND GRAVEL 0 60 VARIED SOFT SILTY SAND 60 100 BROWN SOFT CLAY 100 110 GRAY SOFT SAND CLAY 110 180 VARIED SOFT CLAY W/ BOULDERS 180 280 BRN/RED HARD SAND 280 290 VARIED MEDIUM SANDSTONE 290 330 WHITE MEDIUM										Well Hydrofractured? Yes ☐ No ☐ From To																			
										Casing Type Single casing Joint Welded																			
										Drive Shoe? Yes ☐ No ☒ Above/Below																			
										Casing Diameter Weight Hole Diameter 4 in. To 322 ft. lbs./ft. 8 in. To 330 ft.																			
										Open Hole From ft. To ft.																			
										Screen? ☒ Type plastic Make SLOTTED Diameter Slot/Gauze Length Set 4 in. 25 10 ft. 320 ft. 330 ft.																			
										Static Water Level 110 ft. land surface Measure 10/28/1993																			
										Pumping Level (below land surface) 147 ft. 4 hrs. Pumping at 40 g.p.m.																			
										Wellhead Completion Pitless adapter manufacturer WHITEWATER Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																			
										Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite ft. ft.																			
Nearest Known Source of Contamination feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☐ Yes ☐ No																													
Pump ☐ Not Installed Date Installed 11/03/1993 Manufacturer's name STARITE Model Number HP 1 Volt 230 Length of drop pipe 147 ft Capacity 10 g.p. Typ Submersible																													
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																													
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																													
Miscellaneous First Bedrock Mt.Simon Sandstone Aquifer Mt.Simon Last Strat Mt.Simon Sandstone Depth to Bedrock 290 ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 457024 Y 5028326 Unique Number Verification Address verification Input Date 11/12/2010																													
Angled Drill Hole																													
Well Contractor Bergerson-Caswell 27058 SCHMIDT, L. Licensee Business Lic. or Reg. No. Name of Driller																													
Remarks																													

Minnesota Well Index Report

535895

Printed on 10/02/2026
HE-01205-15