

541405

County Freeborn
Quad Glenville
Quad ID 10D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/22/1995
Update Date 06/02/2023
Received Date 11/17/1994

Well Name LARES, LINDA	Township 102	Range 21	Dir Section W 21	Subsection CBBBDB
Elevation 1295	Elev. Method LiDAR 1m DEM (MNDNR)			
Address Contact RR 1 BOX 45 ALBERT LEA MN 56007				
Stratigraphy Information Geological Material From To (ft.) Color Hardness DRIFT 0 150 SOFT LIMESTONE 150 170 GRAY HARD				
Well Depth 170 ft.				
Depth Completed 170 ft.				
Date Well Completed 10/31/1994				
Drill Method Non-specified Rotary				
Drill Fluid Bentonite				
Use domestic				
Status Active				
Well Hydrofractured? Yes ☐ No ☐				
From To				
Casing Type Single casing				
Joint Welded				
Drive Shoe? Yes ☒ No ☐				
Above/Below				
Casing Diameter 5 in. To 153 ft. 15 lbs./ft.				
Weight				
Hole Diameter 10 in. To 30 ft. 8 in. To 153 ft. 5 in. To 170 ft.				
Open Hole From 153 ft. To 170 ft.				
Screen? ☐ Type Make				
Static Water Level 91 ft. land surface Measure 10/31/1994				
Pumping Level (below land surface) ft. hrs. Pumping at 50 g.p.m.				
Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)				
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks 0 ft. 30 ft.				
Nearest Known Source of Contamination 60 feet <u>Northeas</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No				
Pump ☐ Not Installed Date Installed <u>11/03/1994</u> Manufacturer's name GOULDS Model Number HP <u>0.75</u> Volt <u>220</u> Length of drop pipe <u>108</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>				
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No				
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No				
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock 150 ft Located by Minnesota Department of Health Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 470340 Y 4829936 Unique Number Verification Info/GPS from data Input Date 08/20/2002				
Angled Drill Hole				
Well Contractor Morrison Well Co. 24001 MORRISON, R. Licensee Business Lic. or Reg. No. Name of Driller				

Remarks