

544677

County Brown
Quad Springfield
Quad ID 59B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/07/1995
Update Date 02/14/2014
Received Date

Well Name SCHOTZKO, Elevation 1120 Address C/W Stratigraphy Information Geological Material From To (ft.) Color Hardness LOAM 0 2 BLACK SOFT CLAY 2 18 YELLOW MEDIUM CLAY 18 42 BLUE MEDIUM GRAVEL/SAND 42 69 BROWN CLAY 69 94 BLUE MEDIUM SAND FINE 94 97 WHITE CLAY GUMMY 97 165 BLUE SAND FINE 165 166 GRAY CLAY GUMMY 166 185 BLUE SAND SUPER FINE 185 187 GRAY CLAY GUMMY 187 212 BLUE SAND SUPER FINE 212 215 GRAY CLAY GUMMY 215 220 GRAY SAND FINE 220 225 WHITE					Township 108 Range 34 Dir W Section 28 Subsection BBBDAB		Well Depth 225 ft. Drill Method Non-specified Rotary Use domestic Well Hydrofractured? Yes ☐ No ☐ Casing Type Single casing Drive Shoe? Yes ☐ No ☐ Casing Diameter 5 in. To 220 ft. lbs./ft. Hole Diameter 9.5 in. To 225 ft.		Depth Completed 225 ft. Date Well Completed 11/26/1994 Drill Fluid Bentonite Status Active From To Joint 0 ft. Open Hole From ft. To ft. Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 3 in. 12 5 ft. 220 ft. 225 ft. Static Water Level 40 ft. land surface Measure 11/26/1994 Pumping Level (below land surface) 80 ft. 2 hrs. Pumping at 50 g.p.m. Wellhead Completion Pitless adapter manufacturer MONITOR Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks 0 ft. 200 ft.	
Remarks					Nearest Known Source of Contamination 75 feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☐ Yes ☐ No Pump ☐ Not Installed Date Installed 11/26/1994 Manufacturer's name GOULDS Model Number HP 0.75 Volt 220 Length of drop pipe 100 ft Capacity 10 g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No Miscellaneous First Bedrock Cretaceous undiff. Aquifer Cretaceous, Last Strat Cretaceous undiff. Depth to Bedrock 166 ft Located by Minnesota Geological Survey Locate Method Digitized - scale 1:24,000 or larger (Digitizing Table) System UTM - NAD83, Zone 15, Meters X 344965 Y 4888756 Unique Number Verification Tag on well Input Date 09/01/1998 Angled Drill Hole Well Contractor Steffl C.t. Well Co. 08044 STEFFL, T. Licensee Business Lic. or Reg. No. Name of Driller					
Minnesota Well Index Report			544677		Printed on 08/13/2026 HE-01205-15					