

547615

County Sherburne
Quad Lake
Quad ID 137A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/31/1995
Update Date 02/14/2014
Received Date

Well Name FISHER, DON					Township 34	Range 26	Dir W	Section 9	Subsection BBABBD	Well Depth 140 ft.			Depth Completed 140 ft.			Date Well Completed 09/06/1994																					
Elevation 989 ft.					Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary			Drill Fluid																								
Address C/W 26891 128TH ST MN										Use domestic			Status Active																								
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND</td><td>0</td><td>62</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>62</td><td>81</td><td>BLUE</td><td>MEDIUM</td></tr><tr><td>CLAY (GRAVELLY)</td><td>81</td><td>130</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>WATER SAND</td><td>130</td><td>140</td><td>BROWN</td><td>SOFT</td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	SAND	0	62	BROWN	SOFT	CLAY	62	81	BLUE	MEDIUM	CLAY (GRAVELLY)	81	130	BROWN	MEDIUM	WATER SAND	130	140	BROWN	SOFT	Well Hydrofractured? Yes ☐ No ☐ From To		
										Geological Material	From	To (ft.)	Color	Hardness																							
										SAND	0	62	BROWN	SOFT																							
										CLAY	62	81	BLUE	MEDIUM																							
										CLAY (GRAVELLY)	81	130	BROWN	MEDIUM																							
										WATER SAND	130	140	BROWN	SOFT																							
										Casing Type Single casing			Joint																								
										Drive Shoe? Yes ☐ No ☒ Above/Below																											
										Casing Diameter 4 in. To 130 ft.			Weight lbs./ft.			Hole Diameter 6.2 in. To 140 ft.																					
										Open Hole From ft. To ft.																											
Screen? ☒ Type plastic			Make CRESLINE																																		
Diameter 4 in.			Slot/Gauze 15			Length 10 ft.			Set 130 ft. 140 ft.																												
Static Water Level 18 ft. land surface			Measure			09/06/1994																															
Pumping Level (below land surface) 40 ft. 2 hrs. Pumping at 25 g.p.m.																																					
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To cuttings 38 ft. 130 ft. bentonite ft. 38 ft.																																					
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No																																					
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																					
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 453828 Y 5033936 Unique Number Verification Address verification Input Date 11/12/2010																																					
Angled Drill Hole																																					
Well Contractor Ruppert & Son 27086 CORDELL, T. Licensee Business Lic. or Reg. No. Name of Driller																																					

Minnesota Well Index Report	547615	Printed on 08/13/2026 HE-01205-15
-----------------------------	--------	--------------------------------------