Minnesota Unique Well Number

547626

County Sherburne
Quad Orrock
Quad ID 137B

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date 02/15/1995
Update Date 02/14/2014
Received Date

Well Name	Township	Range	Dir	Section	Subsection
	34	27	W	31	DADDBB

Elevation 948 ft. **Elev. Method** 7.5 minute topographic map (+/- 5 feet)

Address

C/W 23036 185TH ST SW MN

Stratigraphy Information

Geological Material	From	To (ft.)	Color	Hardness
SAND	0	45	GRAY	SOFT
CLAY SAND	45	60	BLUE	MEDIUM
CLAY	60	84	BLUE	MEDIUM
COARSE SAND	84	96	GRAY	MEDIUM

Remarks

Well Depth 96 ft. **Depth Completed** 96 ft. **Date Well Completed** 11/22/1994

Drill Method Non-specified Rotary **Drill Fluid** Bentonite

Use domestic **Status** Active

Well Hydrofractured? Yes ☐ No ☐ **From** **To**

Casing Type Single casing **Joint**

Drive Shoe? Yes ☐ No ☒ **Above/Below**

Casing Diameter	Weight	Hole Diameter
4 in. To 96 ft.	lbs./ft.	6.7 in. To 86 ft.
		4 in. To 90 ft.

Open Hole From ft. To ft.

Screen? ☒ **Type** plastic **Make** CRESTLINE

Diameter	Slot/Gauze	Length	Set	
4 in.	18	10 ft.	86 ft.	96 ft.

Static Water Level

11 ft. land surface Measure 11/22/1994

Pumping Level (below land surface)

25 ft. 3 hrs. Pumping at 30 g.p.m.

Wellhead Completion

Pitless adapter manufacturer MAASS Model

☐ Casing Protection ☐ 12 in. above grade

☐ At-grade (Environmental Wells and Borings ONLY)

Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified

Material	Amount	From	To
bentonite		0 ft.	40 ft.
cuttings		40 ft.	86 ft.

Nearest Known Source of Contamination

75 feet South Direction Septic tank/drain field Type

Well disinfected upon completion? ☒ Yes ☐ No

Pump ☐ Not Installed Date Installed 12/07/1994

Manufacturer's name MYERS

Model Number JS11P HP 0.5 Volt 230

Length of drop pipe 40 ft Capacity 12 g.p. Typ Submersible

Abandoned

Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No

Variance

Was a variance granted from the MDH for this well? ☐ Yes ☐ No

Miscellaneous

First Bedrock Aquifer Quat. buried

Last Strat sand-gray Depth to Bedrock ft

Located by Minnesota Geological Survey

Locate Method GPS SA Off (averaged) (15 meters)

System UTM - NAD83, Zone 15, Meters X 442258 Y 5026553

Unique Number Verification Address verification Input Date 12/06/2010

Angled Drill Hole

Well Contractor

Ruppert & Son 27086 CORDELL, T.

Licensee Business Lic. or Reg. No. Name of Driller