

555618

County Becker
Quad Height Of
Quad ID 258A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/06/1995
Update Date 08/27/2014
Received Date

Well Name MATZ, GEORGE					Township 139	Range 39	Dir W	Section 4	Subsection CCDBCB	Well Depth 60 ft.	Depth Completed 60 ft.	Date Well Completed 10/06/1994
Elevation 1456					Elev. Method		7.5 minute topographic map (+/- 5 feet)					
Address												
C/W HC 10 BOX 93A ROCHERT MN 56578												
Stratigraphy Information												
Geological Material		From	To (ft.)	Color	Hardness							
SAND		0	8	RED	SOFT							
SANDY CLAY		8	19	LT. RED	SOFT							
SAND AND GRAVEL		19	55	LT. BLU	MEDIUM							
SAND FINE		55	60	GRAY	SOFT							
Use domestic Status Active												
Well Hydrofractured? Yes ☐ No ☐ From To												
Casing Type Single casing Joint												
Drive Shoe? Yes ☐ No ☒ Above/Below												
Casing Diameter		Weight		Hole Diameter								
4 in. To		56 ft. 1.9 lbs./ft.		7 in. To 60 ft.								
Open Hole From ft. To ft.												
Screen? ☒ Type stainless Make JOHNSON												
Diameter		Slot/Gauze		Length		Set						
4 in.		10		5 ft.		56 ft. 60 ft.						
Static Water Level												
5 ft.		land surface		Measure		10/06/1994						
Pumping Level (below land surface)												
5 ft.		2 hrs.		Pumping at		20 g.p.m.						
Wellhead Completion												
Pitless adapter manufacturer		MONITOR		Model		4X15N						
☐ Casing Protection		☒ 12 in. above grade										
☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified												
Material		Amount		From		To						
bentonite		3 Sacks		0 ft.		50 ft.						
Nearest Known Source of Contamination												
70 feet		South Direction		Septic tank/drain field		Type						
Well disinfected upon completion?		☒ Yes ☐ No										
Pump ☐ Not Installed Date Installed 10/12/1994												
Manufacturer's name		STARITE										
Model Number		T53W		HP		0.5		Volt		110		
Length of drop pipe		40 ft		Capacity		10 g.p.		Typ		Submersible		
Abandoned												
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No												
Variance												
Was a variance granted from the MDH for this well? ☐ Yes ☐ No												
Miscellaneous												
First Bedrock		sand-gray		Aquifer		Quat. buried		ft				
Last Strat		Depth to Bedrock										
Located by		Minnesota Geological Survey										
Locate Method		Digitized - scale 1:24,000 or larger (Digitizing Table)										
System		UTM - NAD83, Zone 15, Meters		X 300087		Y 5194698						
Unique Number Verification		Information from		Input Date		10/29/1998						
Angled Drill Hole												
Well Contractor												
Krueger Well Drll		03669		KRUEGER, R.								
Licensee Business		Lic. or Reg. No.		Name of Driller								