

561393

County Hennepin
Quad Rockford
Quad ID 121C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 11/27/1996
Update Date 03/08/2015
Received Date

Well Name Township Range Dir Section Subsection 118 24 W 14 ABACCC					Well Depth 264 ft.		Depth Completed 264 ft.		Date Well Completed 10/16/1995				
Elevation 991 ft. Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary		Drill Fluid						
Address Well 6105 WOOD HILL LA INDEPENDENCE MN 55359					Use domestic		Status Active						
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 70 SOFT SAND 70 85 SOFT CLAY 85 250 SOFT SAND 250 264 SOFT					Well Hydrofractured? Yes ☐ No ☐ From To								
					Casing Type Single casing Joint								
					Drive Shoe? Yes ☐ No ☐ Above/Below								
					Casing Diameter Weight Hole Diameter								
					4 in. To 256 ft. lbs./ft. 8 in. To 30 ft.								
					6.2 in. To 264 ft.								
					Open Hole From ft. To ft.								
					Screen? ☒ Type stainless Make HALLIBURTON								
					Diameter Slot/Gauze Length Set								
					2 in. 10 8 ft. 256 ft. 260 ft.								
Static Water Level 80 ft. land surface Measure 10/16/1995													
Pumping Level (below land surface)													
Wellhead Completion Pitless adapter manufacturer WHITEWATER Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)													
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified													
Material Amount From To													
bentonite 3 Sacks ft. 30 ft.													
Nearest Known Source of Contamination feet Direction Type													
Well disinfected upon completion? ☒ Yes ☐ No													
Pump ☐ Not Installed Date Installed 11/22/1995													
Manufacturer's name GOULDS													
Model Number 18LS15412L HP 1.5 Volt 230													
Length of drop pipe 126 ft Capacity 18 g.p. Typ Submersible													
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No													
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No													
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 446939 Y 4987032 Unique Number Verification Address verification Input Date 07/28/2014													
Angled Drill Hole													
Well Contractor Stodola Don Well Co. 27172 MCMAHON, F. Licensee Business Lic. or Reg. No. Name of Driller													