

571654

County Anoka
Quad Nowthen
Quad ID 136C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/31/1997
Update Date 02/14/2014
Received Date 01/26/1995

Well Name 32 Township 24 Range W 19 Dir Section BCAADC Subsection					Well Depth 89 ft.		Depth Completed 89 ft.		Date Well Completed 12/06/1995	
Elevation 873 ft. Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary		Drill Fluid Bentonite			
Address Well 15440 POTAWATOMI ST NW ANDOVER MN 55304					Use domestic		Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness SAND 0 31 BROWN SOFT CLAY 31 60 BROWN MEDIUM WATERSAND 60 89 BROWN SOFT					Well Hydrofractured? Yes ☐ No ☐		From		To	
					Casing Type Single casing		Joint			
					Drive Shoe? Yes ☐ No ☐		Above/Below			
					Casing Diameter 4 in. To 79 ft.		Weight lbs./ft.		Hole Diameter 6.2 in. To 89 ft.	
					Open Hole From ft. To ft.					
					Screen? ☒		Type plastic		Make CRESLINE	
					Diameter 4 in.		Slot/Gauze 18		Length 10 ft.	
					Set 79 ft.		89 ft.			
					Static Water Level 28 ft.		land surface		Measure 10/17/1995	
					Pumping Level (below land surface) 45 ft.		2 hrs.		Pumping at 25 g.p.m.	
Wellhead Completion Pitless adapter manufacturer MAASS Model JC-1 ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)					Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified					
Material cuttings high solids bentonite					Amount 40 ft.		From 89 ft.		To 40 ft.	
Nearest Known Source of Contamination 75 feet South Direction Well disinfected upon completion? ☒ Yes ☐ No					Septic tank/drain field		Type			
Pump ☐ Not Installed Date Installed 12/06/1995 Manufacturer's name MYERS Model Number 102-20 HP Length of drop pipe 60 ft Capacity g.p. Typ Submersible										
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No										
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No										
Miscellaneous First Bedrock sand-brown Last Strat sand-brown Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 469900 Y 5010922 Unique Number Verification Address verification Input Date 08/31/2006										
Angled Drill Hole										
Well Contractor Ruppert & Son 27086 RUPPERT, J. Licensee Business Lic. or Reg. No. Name of Driller										
Remarks NORTH 0.5 SECT.										