

576980

County Chisago
Quad Lindstrom
Quad ID 134A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/15/1997
Update Date 03/24/2014
Received Date

Well Name MIZEJEWSKI,	Township 35	Range 19	Dir W	Section 31	Subsection DACABB	Well Depth 220 ft.	Depth Completed 220 ft.	Date Well Completed 02/15/1996
Elevation 965 ft.	Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Non-specified Rotary	Drill Fluid Qwik gel	
Address Well 17064 ST. CROIX TR TAYLORS FALLS MN						Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 25 BROWN MEDIUM COARSE GRAVEL 25 95 VARIED MEDIUM CLAY, ROCKS 95 147 RED HARD CLAYLAYERS SAND, 147 172 VARIED HARD SAND 172 220 BROWN MEDIUM						Well Hydrofractured? Yes ☐ No ☐ From To		
						Casing Type Single casing Joint Glued		
						Drive Shoe? Yes ☐ No ☒ Above/Below		
						Casing Diameter Weight Hole Diameter 4 in. To 216 ft. lbs./ft. 8 in. To 30 ft. 6.5 in. To 220 ft.		
						Open Hole From ft. To ft.		
						Screen? ☒ Type stainless Make COOK Diameter Slot/Gauze Length Set 4 in. 10 4 ft. 216 ft. 220 ft.		
						Static Water Level 160 ft. land surface Measure 02/15/1996		
						Pumping Level (below land surface) 174 ft. 2 hrs. Pumping at 30 g.p.m.		
						Wellhead Completion Pitless adapter manufacturer MONITOR Model BULLDOG ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 3 Sacks 5 ft. 30 ft. cuttings 30 ft. 216 ft.		
Nearest Known Source of Contamination 55 feet West Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed 02/15/1996 Manufacturer's name AERMOTOR Model Number SD1275 HP 0.75 Volt 230 Length of drop pipe 200 ft Capacity 12 g.p. Typ Submersible								
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No								
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 518851 Y 5035740 Unique Number Verification Address verification Input Date 01/18/2008								
Angled Drill Hole								
Well Contractor Husnik Well Co. 13525 HUSNIK, J. Licensee Business Lic. or Reg. No. Name of Driller								