

579642

County Dakota
Quad Coates
Quad ID 88A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/04/2000
Update Date 05/12/2010
Received Date 11/08/1999

Well Name VIRBLAS, ERVIN 114					Township 18		Range W 6		Dir Section BBBBCA		Subsection		Well Depth 300 ft.		Depth Completed 300 ft.		Date Well Completed 09/07/1999				
Elevation 911 ft.					Elev. Method		7.5 minute topographic map (+/- 5 feet)										Drill Method Non-specified Rotary		Drill Fluid Other		
Address														Use domestic		Status Active					
Well 16048 COATES BL ROSEMOUNT MN 55068														Well Hydrofractured? Yes ☐ No ☐				From		To	
Stratigraphy Information														Casing Type Step down		Joint Welded					
Drive Shoe? Yes ☒ No ☐														Above/Below							
Casing Diameter 4 in. To 278 ft. 10.79 lbs./ft.														Hole Diameter 12 in. To 78 ft. 8 in. To 278 ft. 4 in. To 300 ft.							
Open Hole From 278 ft. To 300 ft.																					
Screen? ☐														Type				Make			
Static Water Level														75 ft. land surface Measure 04/15/1999							
Pumping Level (below land surface)																					
Wellhead Completion																					
Pitless adapter manufacturer MAASS Model 43J																					
☐ Casing Protection ☐ 12 in. above grade																					
☐ At-grade (Environmental Wells and Borings ONLY)																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																					
Material Amount From To																					
neat cement 82 Sacks 0 ft. 278 ft.																					
Nearest Known Source of Contamination																					
105 feet East Direction Septic tank/drain field Type																					
Well disinfected upon completion? ☒ Yes ☐ No																					
Pump ☒ Not Installed Date Installed																					
Manufacturer's name																					
Model Number HP Volt																					
Length of drop pipe ft Capacity g.p. Typ																					
Abandoned																					
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																					
Variance																					
Was a variance granted from the MDH for this well? ☐ Yes ☒ No																					
Miscellaneous																					
First Bedrock Prairie Du Chien Group Aquifer Jordan																					
Last Strat Jordan Sandstone Depth to Bedrock 78 ft																					
Located by Minnesota Geological Survey																					
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or																					
System UTM - NAD83, Zone 15, Meters X 497261 Y 4951468																					
Unique Number Verification Tag on well Input Date 09/13/2005																					
Angled Drill Hole																					
Well Contractor																					
Carlson Well Maher,t 19302 BOB/PAUL																					
Licensee Business Lic. or Reg. No. Name of Driller																					
Remarks																					
DRILLERS: BOB KAASE & PAUL MOELLER.																					
Minnesota Well Index Report										579642				Printed on 08/13/2026 HE-01205-15							