Minnesota Unique Well Number

581797

County Todd
Quad Round
Quad ID 178B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT

Entry Date 08/19/1996
Update Date 02/14/2014
Received Date

Well Name	Township	Range	Dir	Section	Subsection
PAUL, TARRANT	129	33	W	18	ACDDBB

Elevation 1385 ft. **Elev. Method** 7.5 minute topographic map (+/- 5 feet)

Address

C/W 23177 86 CR LONG PRAIRIE MN 56438

Stratigraphy Information

Geological Material	From	To (ft.)	Color	Hardness
TOPSOIL	0	1	BLACK	SOFT
CLAY	1	20	BROWN	MEDIUM
CLAY	20	27	GRAY	HARD
SAND	27	35	BROWN	MEDIUM

Remarks

WELL SEALED IN BACK OF HOUSE.

Well Depth 35 ft. **Depth Completed** 35 ft. **Date Well Completed** 06/20/1996

Drill Method Non-specified Rotary **Drill Fluid** Bentonite

Use domestic **Status** Active

Well Hydrofractured? Yes ☐ No ☐ **From** **To**

Casing Type Single casing **Joint**
Drive Shoe? Yes ☐ No ☐ **Above/Below**

Casing Diameter		Weight		Hole Diameter	
5 in. To 27 ft.		3 lbs./ft.		8.7 in. To 35 ft.	

Open Hole From ft. To ft.

Screen? ☒ **Type** stainless **Make** JOHNSON

Diameter	Slot/Gauze	Length	Set Between	
5 in.	15	8 ft.	27 ft.	35 ft.

Static Water Level

23 ft. land surface Measure Date 06/20/1996

Pumping Level (below land surface)

32 ft. after 1 hrs. Pumping at 8 g.p.m.

Wellhead Completion

Pitless adapter manufacturer MAASS Model

☐ Casing Protection ☐ 12 in. above grade
☐ At-grade (Environmental Wells and Borings ONLY)

Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified

Material	Amount	From	To
high solids bentonite		0 ft.	27 ft.

Nearest Known Source of Contamination

51 feet East Direction Septic tank/drain field Type

Well disinfected upon completion? ☒ Yes ☐ No

Pump ☐ Not Installed Date Installed 06/21/1996

Manufacturer's name OWNER'S PUMP
Model Number HP Volt
Length of drop pipe ft Capacity g.p.m. Type Submersible

Abandoned Wells

Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No

Variance

Was a variance granted from the MDH for this well? ☐ Yes ☒ No

Miscellaneous

First Bedrock Aquifer Quat. buried artes.
Last Strat sand-brown Depth to Bedrock ft.
Located by Minnesota Geological Survey
Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or better)
System UTM - NAD83, Zone 15, Meters X 354158 Y 5094030
Unique Number Verification Information from Input Date 08/14/2003

Angled Drill Hole

Well Contractor Certification

Klimek Bros. Well Drilling, Inc. 21699 KLIMEK, D.
Licensee Business Name Lic. or Reg. No. Name of Driller