

588961

County Isanti
Quad Typo Lake
Quad ID 135A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/22/1997
Update Date 09/05/2014
Received Date 11/25/1996

Well Name VOLLHABER,					Township 34		Range 22		Dir Section W 15		Subsection ADADDD	
Elevation 925 ft.					Elev. Method LiDAR 1m DEM (MNDNR)							
Address												
Contact					9246 168TH AV FOREST LAKE MN 55025							
Well					25829 PIGEON LOFT RD NE STACY MN							
Stratigraphy Information												
Geological Material			From	To (ft.)	Color	Hardness						
SAND			0	38	BROWN							
CLAY			38	50	GRAY							
SAND & GRAVEL			50	84	GRAY							
Well Depth 84 ft.												
Depth Completed 84 ft.												
Date Well Completed 11/19/1996												
Drill Method Non-specified Rotary				Drill Fluid Bentonite								
Use domestic										Status Active		
Well Hydrofractured? Yes ☐ No ☐ From To												
Casing Type Single casing				Joint Glued								
Drive Shoe? Yes ☐ No ☒				Above/Below								
Casing Diameter 4 in. To 80 ft.				Weight lbs./ft.				Hole Diameter 8 in. To 84 ft.				
Open Hole From ft. To ft.												
Screen? ☒ Type stainless Make JOHNSON												
Diameter			Slot/Gauze		Length		Set					
4 in.			20		4 ft.		80 ft.		84 ft.			
Static Water Level 22 ft. land surface Measure 11/19/1996												
Pumping Level (below land surface) 84 ft. 1 hrs. Pumping at 50 g.p.m.												
Wellhead Completion Pitless adapter manufacturer SNAPPY Model 1 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified												
Material				Amount		From		To				
high solids bentonite				2 Sacks		0 ft.		30 ft.				
Nearest Known Source of Contamination 100 feet North Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No												
Pump ☐ Not Installed Date Installed 11/19/1996												
Manufacturer's name MYERS												
Model Number			2 WIRE		HP 0.5		Volt 230					
Length of drop pipe			40 ft		Capacity 12 g.p.		Typ Submersible					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No												
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No												
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand +larger-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 495142 Y 5031403 Unique Number Verification Address verification Input Date 07/22/2014												
Angled Drill Hole												
Well Contractor Barott Drilling 02303 BAROTT, G. Licensee Business Lic. or Reg. No. Name of Driller												
Remarks												