

591128

County Anoka
Quad Coon Lake
Quad ID 135C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 07/30/1997
Update Date 02/14/2014
Received Date 01/03/1997

Well Name HREHA, JAN					Township 32		Range 23		Dir Section W 12		Subsection BAAACA	
Elevation 905 ft.		Elev. Method 7.5 minute topographic map (+/- 5 feet)										
Address												
C/W 17234 LEVER ST NE HAM LAKE MN 55304												
Stratigraphy Information												
Geological Material		From	To (ft.)	Color	Hardness							
SAND		0	20	BROWN								
SAND		20	46	GRAY								
CLAY		46	58	GRAY								
SAND		58	80	BROWN								
Well Depth 80 ft. Depth Completed 80 ft. Date Well Completed 11/22/1996												
Drill Method Non-specified Rotary		Drill Fluid Bentonite										
Use domestic		Status Active										
Well Hydrofractured?				Yes ☐		No ☐		From		To		
Casing Type Single casing		Joint Glued										
Drive Shoe?		Yes ☐		No ☒		Above/Below						
Casing Diameter		Weight		Hole Diameter								
4 in. To		76 ft.		lbs./ft.				8 in. To 80 ft.				
Open Hole From ft. To ft.												
Screen? ☒		Type stainless		Make JOHNSON								
Diameter		Slot/Gauze		Length		Set						
4 in.		10		4 ft.		76 ft.		80 ft.				
Static Water Level												
11 ft.		land surface		Measure		11/22/1996						
Pumping Level (below land surface)												
80 ft.		1 hrs.		Pumping at		40 g.p.m.						
Wellhead Completion												
Pitless adapter manufacturer		SNAPPY		Model		1"						
☐ Casing Protection		☒ 12 in. above grade										
☐ At-grade (Environmental Wells and Borings ONLY)												
Grouting Information		Well Grouted?		☒ Yes		☐ No		☐ Not Specified				
Material		Amount		From		To						
high solids bentonite		2 Sacks		0 ft.		30 ft.						
Nearest Known Source of Contamination												
60 feet		South Direction		Septic tank/drain field		Type						
Well disinfected upon completion?		☒ Yes		☐ No								
Pump ☐ Not Installed		Date Installed		12/02/1996								
Manufacturer's name		MEYERS										
Model Number		2 WIRE		HP		0.5		Volt		230		
Length of drop pipe		40 ft		Capacity		12 g.p.		Typ		Submersible		
Abandoned												
Does property have any not in use and not sealed well(s)?		☐ Yes		☒ No								
Variance												
Was a variance granted from the MDH for this well?		☐ Yes		☒ No								
Miscellaneous												
First Bedrock		Aquifer		Quat. Water								
Last Strat		sand-brown		Depth to Bedrock		ft						
Located by		Minnesota Geological Survey										
Locate Method		GPS SA Off (averaged) (15 meters)										
System		UTM - NAD83, Zone 15, Meters		X 487988		Y 5014401						
Unique Number Verification		Address verification		Input Date		02/08/2010						
Angled Drill Hole												
Well Contractor												
Barott Drilling		02303		BAROTT, G								
Licensee Business		Lic. or Reg. No.		Name of Driller								
Minnesota Well Index Report				591128		Printed on 08/13/2026 HE-01205-15						