

591746

County Jackson
Quad Lakefield
Quad ID 17D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/22/2000
Update Date 08/17/2026
Received Date 09/02/1998

Well Name SVOBODA,	Township 101	Range 35	Dir W	Section 6	Subsection BDADBB	Well Depth 448 ft.	Depth Completed 448 ft.	Date Well Completed 02/18/1998
Elevation 1503	Elev. Method LiDAR 1m DEM (MNDNR)				Drill Method Non-specified Rotary	Drill Fluid Bentonite		
Address C/W RR 3 BOX 260 JACKSON MN 56143						Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness DIRT 0 1 BLACK SOFT CLAY 1 40 BROWN SOFT CLAY 40 99 BLUE MEDIUM PEA ROCK 99 100 BROWN SOFT CLAY 100 250 BLUE MEDIUM CLAY 250 270 BLUE HARD SAND 270 272 GRAY MEDIUM CLAY 272 310 BROWN HARD CLAY 310 400 BLUE HARD SHALE 400 417 BLACK HARD SAND 417 448 BROWN MEDIUM						Well Hydrofractured? Yes ☐ No ☐ From To		
						Casing Type Step down Joint		
						Drive Shoe? Yes ☐ No ☒ Above/Below		
						Casing Diameter Weight Hole Diameter 5 in. To 438 ft. lbs./ft. 9 in. To 448 ft. 5 in. To 195 ft. lbs./ft.		
						Open Hole From ft. To ft.		
						Screen? ☒ Type stainless Make COOK Diameter Slot/Gauze Length Set 6 in. 15 10 ft. 438 ft. 448 ft.		
						Static Water Level 294 ft. land surface Measure 02/18/1998		
						Pumping Level (below land surface) 300 ft. 16 hrs. Pumping at 15 g.p.m.		
						Wellhead Completion Pitless adapter manufacturer MAAS Model 5X1.25 ☒ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 22 Sacks 0 ft. 428 ft.		
Nearest Known Source of Contamination <u>57</u> feet <u>Southwes</u> Direction <u>Barnyard</u> Type Well disinfected upon completion? ☒ Yes ☐ No						Pump ☐ Not Installed Date Installed <u>02/19/1998</u> Manufacturer's name WEBTROL Model Number <u>102S1520B</u> HP <u>1.5</u> Volt <u>230</u> Length of drop pipe <u>340</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>		
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No						Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No		
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock 400 ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:12,000) (>15 meters) System UTM - NAD83, Zone 15, Meters X 331611 Y 4827650 Unique Number Verification Site Plan Input Date 07/24/2025						Angled Drill Hole		
Well Contractor Jerry's Well Co. 90421 CHRISTENSON, Licensee Business Lic. or Reg. No. Name of Driller								