

592109

County Morrison
Quad Ramey NW
Quad ID 174B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/20/1997
Update Date 02/14/2014
Received Date

Well Name MOREN, JESS	Township 39	Range 29	Dir W	Section 11	Subsection DBBDBA	Well Depth 73 ft.	Depth Completed 73 ft.	Date Well Completed 12/23/1996
Elevation 1310	Elev. Method 7.5 minute topographic map (+/- 5 feet)					Drill Method Cable Tool	Drill Fluid	
Address Well 35524 87TH ST PIERZ MN 56364						Use domestic	Status Active	
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☐	From	To
						Casing Type Single casing	Joint Threaded	
						Drive Shoe? Yes ☒ No ☐	Above/Below	
Geological Material						Casing Diameter	Weight	Hole Diameter
TOPSOIL						4 in. To	69 ft. 11 lbs./ft.	4 in. To 73 ft.
HARDPAN								
HARDPAN								
SAND, GRAVEL &								
						Open Hole	From	To
						Screen? ☒	Type stainless	Make JOHNSON
						Diameter	Slot/Gauze	Length
						4 in.	12	4 ft. 69 ft. 73 ft.
						Static Water Level		
						12 ft.	land surface	Measure 12/23/1996
						Pumping Level (below land surface)		
						68 ft.	1 hrs.	Pumping at 10 g.p.m.
						Wellhead Completion		
						Pitless adapter manufacturer	MAASS	Model
						☐ Casing Protection	☒ 12 in. above grade	
						☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information	Well Grouted?	☐ Yes ☒ No ☐ Not Specified
						Nearest Known Source of Contamination		
						70 feet	West Direction	Septic tank/drain field Type
						Well disinfected upon completion?	☒ Yes ☐ No	
						Pump ☐ Not Installed	Date Installed	12/26/1996
						Manufacturer's name	GOULDS	
						Model Number	8SB05126-	HP 0.5 Volt 230
						Length of drop pipe	60 ft	Capacity 8 g.p. Typ Submersible
						Abandoned		
						Does property have any not in use and not sealed well(s)?	☐ Yes ☒ No	
						Variance		
						Was a variance granted from the MDH for this well?	☐ Yes ☒ No	
						Miscellaneous		
						First Bedrock	Aquifer	Quat. buried
						Last Strat	sand +larger	Depth to Bedrock ft
						Located by	Minnesota Geological Survey	
						Locate Method	Digitization (Screen) - Map (1:24,000) (15 meters or	
						System	UTM - NAD83, Zone 15, Meters	X 428662 Y 5082038
						Unique Number Verification	Address verification	Input Date 07/11/2000
						Angled Drill Hole		
						Well Contractor		
						Donabauer Well	73668	DONABAUER, G.
						Licensee Business	Lic. or Reg. No.	Name of Driller