

594905

County Hennepin
Quad Rockford
Quad ID 121C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/29/1999
Update Date 03/13/2015
Received Date

Well Name	Township	Range	Dir	Section	Subsection	Well Depth	Depth Completed	Date Well Completed			
	118	24	W	23	CCADBB	126 ft.	126 ft.	11/07/1997			
Elevation	976 ft.	Elev. Method	LiDAR 1m DEM (MNDNR)								
Address						Use	domestic	Status	Active		
C/W						6240 12 HY W MAPLE PLAIN MN 55359					
Stratigraphy Information						Well Hydrofractured?	Yes ☐	No ☐	From	To	
Geological Material						Casing Type	Single casing	Joint	Glued		
CLAY						Drive Shoe?	Yes ☐	No ☒	Above/Below		
CLAY						Casing Diameter	Weight	Hole Diameter			
SAND						4 in. To	121 ft.	lbs./ft.	8 in. To	126 ft.	
						Open Hole	From	ft.	To	ft.	
						Screen?	☒	Type	telescoping	Make	JAYCO
						Diameter	Slot/Gauze	Length	Set		
						3 in.	18	5 ft.	ft.	ft.	
						Static Water Level					
						53 ft.	land surface	Measure	11/07/1997		
						Pumping Level (below land surface)					
						ft.	hrs.	Pumping at	100	g.p.m.	
						Wellhead Completion					
						Pitless adapter manufacturer	MAASS	Model			
						☐ Casing Protection	☒ 12 in. above grade				
						☐ At-grade (Environmental Wells and Borings ONLY)					
						Grouting Information					
						Well Grouted?	☒ Yes	☐ No	☐ Not Specified		
						Material	Amount	From	To		
						neat cement	8 Sacks	9	ft. 51	ft.	
						Nearest Known Source of Contamination					
						feet	Direction			Type	
						Well disinfected upon completion?	☒ Yes	☐ No			
						Pump	☐ Not Installed	Date Installed	06/24/1998		
						Manufacturer's name	MEYERS				
						Model Number	HP	1	Volt		
						Length of drop pipe	84 ft	Capacity	20 g.p.	Typ	Submersible
						Abandoned					
						Does property have any not in use and not sealed well(s)?					
						☐ Yes ☒ No					
						Variance					
						Was a variance granted from the MDH for this well?					
						☐ Yes ☒ No					
						Miscellaneous					
						First Bedrock	Aquifer				
						Last Strat	sand-gray	Depth to Bedrock	Quat. buried	ft	
						Located by					
						Minnesota Geological Survey					
						Locate Method					
						GPS SA Off (averaged) (15 meters)					
						System	UTM - NAD83, Zone 15, Meters	X	446232	Y	4984345
						Unique Number Verification	Address verification	Input Date	07/28/2014		
						Angled Drill Hole					
						Well Contractor					
						Stevens Well Drilling Co. Inc.	86654	SWEARINGEN, P			
						Licensee Business	Lic. or Reg. No.	Name of Driller			