

595969

County Stearns
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/01/1998
Update Date 04/08/2014
Received Date

Well Name MOLITOR,					Township 123	Range 29	Dir W	Section 29	Subsection null	Well Depth 223 ft.			Depth Completed 223 ft.			Date Well Completed 05/23/1997					
Elevation					Elev. Method					Drill Method Non-specified Rotary			Drill Fluid Bentonite								
Address										Use domestic			Status Active								
Well 12192 210TH ST COLD SPRING MN 56320										Well Hydrofractured?			Yes ☐		No ☐		From		To		
Contact P.O. BOX 392 ROCKVILLE MN 56369										Casing Type Single casing			Joint								
Stratigraphy Information										Drive Shoe?			Yes ☐		No ☒		Above/Below				
Geological Material					From	To (ft.)	Color	Hardness		Casing Diameter			Weight			Hole Diameter					
CLAY					0	21	BROWN	MEDIUM		4 in. To			208 ft. lbs./ft.			8.8 in. To 223 ft.					
SAND, MUD					21	42	BROWN	MEDIUM													
CLAY					42	202	GRAY	HARD													
SAND, ROCK					202	216	GRAY	M.HARD													
SAND, WOOD					216	223	GRAY	MEDIUM													
										Open Hole			From		ft.		To		ft.		
										Screen? ☒		Type plastic		Make							
										Diameter		Slot/Gauze		Length		Set					
										4 in.		12		15 ft.		208 ft.		223 ft.			
										Static Water Level											
										50 ft.		land surface				Measure		05/23/1997			
										Pumping Level (below land surface)											
										60 ft.		1 hrs.		Pumping at		20		g.p.m.			
										Wellhead Completion											
										Pitless adapter manufacturer			MONITOR		Model		SNAPPY				
										☐ Casing Protection			☒ 12 in. above grade								
										☐ At-grade (Environmental Wells and Borings ONLY)											
										Grouting Information			Well Grouted?		☒ Yes		☐ No		☐ Not Specified		
										Material		Amount		From		To					
										bentonite		4 Cubic yards		0		ft. 208		ft.			
										Nearest Known Source of Contamination											
										100 feet		North Direction		Septic tank/drain field		Type					
										Well disinfected upon completion?			☒ Yes		☐ No						
										Pump ☐ Not Installed			Date Installed		07/01/1997						
										Manufacturer's name			AERMOTOR								
										Model Number		SD1250		HP		0.5		Volt		230	
										Length of drop pipe		80 ft		Capacity		12 g.p.		Typ		Submersible	
										Abandoned											
										Does property have any not in use and not sealed well(s)?			☐ Yes		☒ No						
										Variance											
										Was a variance granted from the MDH for this well?			☐ Yes		☒ No						
										Miscellaneous											
										First Bedrock			Aquifer								
										Last Strat			Depth to Bedrock			ft					
										Located by											
										Locate Method											
										System		UTM - NAD83, Zone 15, Meters		X		Y					
										Unique Number Verification						Input Date					
										Angled Drill Hole											
										Well Contractor											
										Fischer Well Co.			73135		JACK FISCHER						
										Licensee Business			Lic. or Reg. No.		Name of Driller						
Minnesota Well Index Report					595969					Printed on 08/13/2026 HE-01205-15											